

# FREQUENCY-CONTROLLED WIRELESS PASSIVE MICROFLUIDIC DEVICES

MARWAN NAFEA MINJAL

A thesis submitted in fulfillment of the  
requirements of the award of the degree of  
Doctor of Philosophy (Electrical Engineering)

Faculty of Electrical Engineering  
Universiti Teknologi Malaysia

MAY 2018

*I dedicate this thesis to my beloved family whose love, kindness, patience and prayer  
have brought me this far*

## ACKNOWLEDGEMENT

First and foremost, my unlimited and sincere appreciation goes to the Lord of the seven heavens and earth ALLAH (SWT) for His endless mercies, blessings and guidance through from birth till now and forever.

I would like to express my deepest gratitude and thanks to Assoc. Prof. Ir. Dr. Mohamed Sultan Mohamed Ali and Dr. Amirjan Nawabjan, my honorable supervisors, for giving me the opportunity to work in their wonderful research groups. Their continuous guidance, committed support and invaluable advice throughout my studies have made the completion of this work possible. Their enthusiasm and hard work caused me to awake every day with enthusiasm for what I was to do next. I have learned a great deal from them on every aspect of academics including teaching, research, manuscript writing, grant applications and management skills and I hope to learn much more from them.

I sincerely thank all the professors and lecturers who have taught me for their invaluable lessons. In addition, I would also like to thank all of my friends and colleagues, especially Amirah 'Aisha Badrul Hisham for her valuable assistance in the preparation of the thesis.

Last but not least, I owe more than I can express to my parents and my sister for the greatest support and love I have received, without them I would have never been able to accomplish this thesis.

## ABSTRACT

Microfluidics is a promising technology that is increasingly attracting the attention of researchers due to its high efficiency and low-cost features. Micropumps, micromixers, and microvalves have been widely applied in various biomedical applications due to their compact size and precise dosage controllability. Nevertheless, despite the vast amount of research reported in this research area, the ability to implement these devices in portable and implantable applications is still limited. To date, such devices are constricted to the use of wires, or on-board power supplies, such as batteries. This thesis presents novel techniques that allow wireless control of passive microfluidic devices using an external radiofrequency magnetic field utilizing thermopneumatic principle. Three microfluidic devices are designed and developed to perform within the range of implantable drug-delivery devices. To demonstrate the wireless control of microfluidic devices, a wireless implantable thermopneumatic micropump is presented. Thermopneumatic pumping with a maximum flow rate of  $2.86 \mu\text{L}/\text{min}$  is realized using a planar wirelessly-controlled passive inductor-capacitor heater. Then, this principle was extended in order to demonstrate the selective wireless control of multiple passive heaters. A passive wirelessly-controlled thermopneumatic zigzag micromixer is developed as a mean of a multiple drug delivery device. A maximum mixing efficiency of 96.1% is achieved by selectively activating two passive wireless planar inductor-capacitor heaters that have different resonant frequency values. To eliminate the heat associated with aforementioned wireless devices, a wireless piezoelectric normally-closed microvalve for drug delivery applications is developed. A piezoelectric diaphragm is operated wirelessly using the wireless power that is transferred from an external magnetic field. Valving is achieved with a percentage error as low as 3.11% in a 3 days long-term functionality test. The developed devices present a promising implementation of the reported wireless actuation principles in various portable and implantable biomedical applications, such as drug delivery, analytical assays, and cell lysis devices.

## ABSTRAK

Bendalir-mikro adalah teknologi yang berpotensi tinggi dan semakin menarik perhatian penyelidik kerana ciri-ciri kecekapan yang tinggi dan kos yang rendah. Pam, pencampur dan injap-mikro telah digunakan secara meluas dalam pelbagai aplikasi bioperubatan kerana saiz yang kecil dan kebolehkawalan dos yang tepat. Meskipun banyak penyelidikan dilaporkan dalam bidang ini, aplikasinya dalam peranti mudah alih dan boleh implan masih terhad. Sehingga kini, peranti sedemikian terbatas kepada penggunaan wayar, atau bekalan kuasa seperti bateri. Tesis ini melaporkan teknik novel yang membolehkan kawalan tanpa wayar bagi peranti bendalir-mikro pasif termopneumatik dengan menggunakan medan magnet. Tiga peranti bendalir-mikro direka bentuk dan dibangunkan untuk kegunaan dalam lingkungan peranti perembesan ubat boleh implan. Untuk mendemonstrasi kawalan tanpa wayar peranti bendalir-mikro, satu pam mikro termopneumatik boleh implan dilaporkan. Pam termopneumatik dengan kadar perembesan maksimum  $2.86 \mu\text{L}/\text{min}$  direalisasikan dengan menggunakan pemanasan induktor-kapasitor pasif satah yang dikendalikan tanpa wayar. Kemudian, prinsip ini dikembangkan untuk menunjukkan kawalan tanpa wayar bagi pengaktifan terpilih beberapa pemanas pasif. Sebuah pencampur-mikro termopneumatik pasif berliku tanpa wayar dibangunkan sebagai satu alat peranti perembesan ubat implan berganda. Kadar pencampuran maksimum 96.1 % dicapai dengan mengaktifkan dua pemanas pasif tanpa wayar yang mempunyai nilai frekuensi resonan yang berbeza secara terpilih. Untuk menyingkirkan kesan haba yang berkaitan dengan peranti tanpa wayar tersebut, satu injap-mikro piezoelektrik biasa-tertutup dibina untuk aplikasi perembesan ubat implan. Penginjapan dicapai dengan kadar ralat serendah 3.11 % untuk pengujian jangka panjang selama tiga hari. Peranti yang dibangunkan menunjukkan potensi penggunaan prinsip-prinsip pergerakan tanpa wayar dalam pelbagai aplikasi bioperubatan mudah alih dan boleh implan seperti perembesan ubat, ujian analisis dan peranti sel lisis.

## TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	<b>DECLARATION</b>	<b>ii</b>
	<b>DEDICATION</b>	<b>iii</b>
	<b>ACKNOWLEDGEMENT</b>	<b>iv</b>
	<b>ABSTRACT</b>	<b>v</b>
	<b>ABSTRAK</b>	<b>vi</b>
	<b>TABLE OF CONTENTS</b>	<b>vii</b>
	<b>LIST OF TABLES</b>	<b>xi</b>
	<b>LIST OF FIGURES</b>	<b>xii</b>
	<b>LIST OF ABBREVIATIONS</b>	<b>xvii</b>
	<b>LIST OF SYMBOLS</b>	<b>xx</b>
	<b>LIST OF APPENDICES</b>	<b>xxv</b>
<b>INTRODUCTION</b>		<b>1</b>
1.1	Introduction	1
1.2	Problem Statement	3
1.3	Research Objectives	4
1.4	Scope of Research	5
1.5	Research Contributions	6
1.6	Potential Impact of the Research	7
1.7	Methodology	7
1.8	Thesis Outline	12
<b>LITERATURE REVIEW</b>		<b>13</b>
2.1	Introduction	13
2.2	Microfluidics	13

2.3	Laminar Flow	14
2.4	Microfluidic Devices	17
2.5	Micropumps	18
	2.5.1 Classification of Micropumps	18
	2.5.2 Microactuators for Microfluidic Devices	21
	2.5.3 Thermopneumatic Micropumps	22
2.6	Micromixers	24
	2.6.1 Classification of Micromixers	25
	2.6.2 Zigzag Passive Micromixers	27
	2.6.3 Pulsatile Flows in Micromixers	28
2.7	Microvalves	29
	2.7.1 Classification of Microvalves	29
	2.7.2 Piezo-Actuated Microvalves	31
2.8	Powering Methods for Portable and Implantable Microfluidic Devices	33
2.9	Summary	37

## **WIRELESSLY CONTROLLED THERMOPNEUMATIC PASSIVE**

	<b>MICROPUMP</b>	<b>38</b>
3.1	Introduction	38
3.2	Design and Working Principle of the Wireless Thermopneumatic Micropump	39
3.3	Theoretical Modeling of the Wireless Thermopneumatic Micropump	40
	3.3.1 Design of the Planar Resonant Heater	40
	3.3.2 Thermal Analysis of the Device	42
3.4	Numerical Simulation of the Thermopneumatic Micropump	46
3.5	Fabrication of the Thermopneumatic Micropump	48
3.6	Experimental Results and Discussion of the Wireless thermopneumatic Micropump	50
	3.6.1 Dynamic Heat Transfer Profile of the Thermopneumatic Micropump	50

3.6.2	Wireless Thermopneumatic Actuation Characterization	54
3.7	Summary	61
<b>WIRELESSLY-CONTROLLED PASSIVE ZIGZAG MICROMIXER</b>		<b>62</b>
4.1	Introduction	62
4.2	Design and Working Principle of the Wireless Passive Zigzag Micromixer	63
4.3	Theoretical Modeling of the Wireless Passive Zigzag Micromixer	64
4.4	Finite Element Analysis of the Thermopneumatic Zigzag Micromixer	65
4.5	Fabrication of the Wireless Thermopneumatic Passive Zigzag Micromixer	68
4.6	Experimental Results and Discussion of the Wireless Thermopneumatic Micromixer	71
4.6.1	Dynamic Heat Transfer Profile of the Thermopneumatic Zigzag Micromixer	72
4.6.2	Thermopneumatic Actuation and Mixing Characterization	77
4.7	Summary	87
<b>WIRELESSLY-CONTROLLED NORMALLY-CLOSED PIEZO- ACTUATED MICROVALVE</b>		<b>88</b>
5.1	Introduction	88
5.2	Design and Working Principle of the Wireless Normally-Closed Piezo-Actuated Microvalve	89
5.3	Theoretical Model of the Wirelessly-Controlled Normally-Closed Piezo-Actuated Microvalve	90
5.3.1	Design of the WPT System for the Wireless Piezo-Actuated Microvalve	91
5.3.2	Modeling of the PEA	94
5.3.3	Design of the Reservoir	95
5.3.4	Immersion in PBS Solution	97



5.4	Finite Element Analysis	98
5.5	Fabrication of the Wireless Normally-Closed Piezo-Actuated microvalve	100
5.6	Experimental Results and Discussion of the Wireless Normally-Closed Piezo-Actuated Microvalve	102
5.6.1	Wired Optimal $f_0$ Characterization of the Piezo-Actuated Microvalve	104
5.6.2	Wireless Actuation Characterization of the Piezo-Actuated Microvalve	106
5.6.3	Wireless Valving Performance	108
5.7	Summary	113
	<b>CONCLUSIONS AND FUTURE WORK</b>	<b>115</b>
6.1	Conclusions	115
6.2	Future Work	118
6.3	List of Publications	119
	<b>REFERENCES</b>	<b>121</b>
	<b>APPENDIX A</b>	<b>146</b>
	<b>Figure 2.4 Reuse Permission</b>	<b>146</b>
	Appendix A	146

**LIST OF TABLES**

<b>TABLE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
2.1	A comparison of the microactuator type, working principle, efficiency, and energy density	22
2.2	Comparison of thermopneumatic micropumps	23
2.3	Selected powering approaches for implantable devices	35

## LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1.1	General methodology steps followed in this thesis	11
2.1	Laminar flow velocity profile in a microchannel under a pressure gradient	16
2.2	General classification of micropumps	19
2.3	General classification of micromixers	25
2.4	Planar designs for mixing with chaotic advection: (a) obstacles on wall, (b) obstacles in the channel, and (c) a zigzag-shaped channel. Reproduced with permission from [67]	26
2.5	General classification of microvalves	30
2.6	Powering methods for implantable microfluidic devices	33
3.1	Schematic diagram of a RF powered thermopneumatic micropump with (a) device setup with an external coil (including a close-up view of the fluid directing channel) (b) a cross section view of the pump, showing frequency-selective working principle using external RF field (not to scale)	39
3.2	(a) Sample layout of the LC circuit design (not to scale) (b) equivalent circuit of the LC heater	41
3.3	Simulation of thermopneumatic pump (a) temperature profile of the device (b) cross section temperature plot from point $A_1$ to $A_2$	47
3.4	Fabrication steps of the micropump	48
3.5	Fabrication results of the developed thermopneumatic micropump	49

3.6	Wireless setup for micropump characterization	50
3.7	IR image showing the temperature distribution along the line A-A' and B-B' at the 10 <sup>th</sup> second after activation	52
3.8	Dynamic heat transfer behavior of the LC wireless heater to the heating chamber	52
3.9	(a) Rise time response; (b) heat transfer coefficient behavior of the heating chamber at different electrical RF heating powers	54
3.10	Micropump pumped volume (a) flow transportation of the developed device from the reservoir to the outlet port (b) transient behavior	55
3.11	Flow performance of the developed micropump (a) flow rate characteristic at different RF power (b) flow velocity at RF power 0.22 W	57
3.12	Two pumping strokes characteristic of the developed micropump	58
3.13	Micropump back pressure with RF frequency variation	59
3.14	Images of the wireless controlled release of the developed prototype immersed in distilled water with (a) inactive state; (b) bubble released due to the excitation of RF field at the output power of 1.5 W; (c) dye released showing the expansion of air in the heating chamber; (d) the dye flow stops when the RF power was turned off	60
4.1	Schematic diagram of the developed micromixer: (a) device setup with an external coil (including a close-up view of the fluid-directing channel), (b) working principle of selective activation of heaters 1 and 2 by tuning $f_m$	63
4.2	A three-dimensional model of the micromixer showing the temperature distribution profile along the device length 50 s after activating heater 1	67
4.3	The simulated temporal response of the temperature of heater 1 and the temperature and resultant deformation of air chamber 1 after 50 s from activating heater 1	68

4.4	Fabrication steps of the device	69
4.5	Fabrication results: (a) master mold, (b) fabricated LC heaters, (c) fabricated micromixer	70
4.6	(a) Measured resonant frequencies of the fabricated heaters, (b) experimental setup for the micromixer characterization	72
4.7	Dynamic heat transfer of the LC heater 1 air chamber 1	73
4.8	Experimental temperature distribution profile of the fabricated LC heaters 50 s after activating heater 1. (a) Thermal image. (b) Temperature profile at the center of the LC wireless heaters (line B–B') and the edge of the LC wireless heaters (line C–C')	75
4.9	Temperature distribution profile along the device length 50 s after activating heater 1. (a) Experimental thermal image of the top view of the micromixer. (b) Simulation and experimental results of the temperature profile along the line A–A'	76
4.10	Simulated and experimentally measured temporal response of the temperature of heater 1 and the resultant deformation of heating chamber 1 after 50 s from activating heater 1	77
4.11	Thermal and microscope images with close-up grayscale images of the mass fraction distribution after (a) 50 s (heater 1 activated), (b) 100 s (heater 2 activated), (c) 105 s (heater 1 activated)	78
4.12	Experimental results of heating and concentration (at position D–D') versus time	79
4.13	Effect of activation patterns on the mixing efficiency. (a) Four activation patterns. (b) Numerical and experimental results of the mixing efficiency using the four activation patterns over 140 s	81
4.14	Numerical and experimental results of the mixing efficiency and pressure drop at the outlet for different $Re$ values	82

4.15	Velocity–vector plots on the cross-sectional plane of the microchannel at position D–D’ (Figure 4. 11) and $Re$ values of (a) 0.1. (b) 1. (c) 10	84
4.16	Numerical and experimental results of the mixing efficiency along the axial mixing length for $Re = 0.1, 1, \text{ and } 10$	85
4.17	Experimental results of flow rate and top PDMS layer deformation when using different PDMS thicknesses and RF powers	86
5.1	Design and working principle of the device. (a) 3D diagram of the device. (b) Close-up view of the top and bottom parts. (c) Closed microvalve. (d) Opened microvalve (not to scale)	90
5.2	Schematic of the equivalent circuit of the WPT link	91
5.3	Simulation results of the valving performance with a visually-scaled deformation	99
5.4	Fabrication steps of the device	100
5.5	Fabrication results. (a) Top and bottom molds. (b) The device is inactive. (c) The device is active	102
5.6	Measured resonant frequencies of the transmitting and the device circuits	103
5.7	Experimental setup for the (a) air test. (b) PBS immersion test	104
5.8	Simulated and measured wired characterization of $f_o$	105
5.9	Theoretical and measured (a) deformation vs. time (b) deformation vs. voltage of the coupled top part	107
5.10	Measured force and remaining volume values for reservoirs with different thickness values	108
5.11	Temporal response of the flow rate and dispensed volume into air and PBS solution	109
5.12	Numerical simulation and experimental results of the input pressure vs. the flow rate for air and PBS solution tests	110
5.13	Measured average flow rates and total volumes delivered during the programmed short-term delivery into air (red) and PBS solution (blue)	111

5.14	Fluid release into PBS solution during the programmed short-term delivery	111
5.15	Programmed flow rate long-term functionality test for air and PBS devices	112

**LIST OF ABBREVIATIONS**

°C	-	Degrees Celsius
3D	-	Three-dimensional
A	-	Ampere
AC	-	Alternating current
CAD	-	Computer-aided design
C	-	Capacitor
cm	-	Centimeter
cm <sup>2</sup>	-	Squared centimeter
cm <sup>3</sup>	-	Cubic centimeter
DI	-	Deionized
DNA	-	Deoxyribonucleic acid
Exp.	-	Experimental
F	-	Farad
FEA	-	Finite element analysis
g	-	Gram
H	-	Henry
h	-	Hour
Hz	-	Hertz
IR	-	Infrared
K	-	Kelvin
k	-	Kilo
kg	-	Kilogram
kHz	-	Kilohertz
kPa	-	Kilopascal
kΩ	-	Kiloohm
L	-	Inductor
LC	-	Inductor-capacitor



LOC	-	Lab-on-a-chip
m	-	Meter
mA	-	Milliampere
M	-	Mega
MEMS	-	Microelectromechanical systems
mH	-	Millihenry
MHz	-	Mega hertz
min	-	Minute
mm	-	Millimetre
mm <sup>2</sup>	-	Squared millimeter
mm <sup>3</sup>	-	Cubic millimeter
mW	-	Milliwatt
n	-	Nano
N	-	Newton
nH	-	Nanohenry
nL	-	Nanoliter
Pa	-	Pascal
PBS	-	Phosphate buffered saline
PC	-	Polycarbonate
PDMS	-	Polydimethylsiloxane
PEA	-	Piezoelectric actuator
pF	-	Picofarad
PI	-	Polyimide
PMMA	-	Poly(methyl methacrylate)
POC	-	Point-of-care
Ref.	-	Reference
RF	-	Radio frequency
rpm	-	Revolutions per minute
s	-	Second
Sim.	-	Simulation
SMA	-	Shape memory alloy
V	-	Volt
W	-	Watt
WPT	-	Wireless power transfer

$\mu\text{L}$	-	Microliter
$\mu\text{m}$	-	Micrometre
$\mu\text{N}$	-	Micronewton
$\mu\text{TAS}$	-	Micro total analysis systems

## LIST OF SYMBOLS

$\mu_f$	-	Fluid viscosity
$A_2$	-	Cross-sectional area of the device coil
$A_C$	-	Cross-sectional area of the microchannel
$A_{Co}$	-	cross-sectional area of the coil
$A_{PDMS}$	-	Cross sectional surface area between the LC wireless heater and the heating chamber
$A_{Pl}$	-	Area of the parallel plates of the capacitor
$A_v$	-	Polynomial of unknown vibration parameters
$A_W$	-	Area of the top wall of the chamber
$b'$	-	Damper coefficient of the piezoelectric actuator and coupled PDMS layers
$B_v$	-	Polynomial of output lag vibration parameters
$c$	-	Molar concentration
$\bar{c}$	-	Mean molar concentration of a fully mixed solution
$c_{ni}$	-	Molar concentration at a point $ni$
$C_P$	-	Capacitance of the piezoelectric actuator
$C_{par}$	-	Parasitic capacitance
$C_T$	-	Tuning capacitor on the transmitter side
$C_{th}$	-	Effective heat capacity of the air chamber
$C_{total}$	-	Total capacitance of the planar heater
$D$	-	Diffusion coefficient
$d$	-	Piezoelectric material constant
$D_{2,j}$	-	Distance between the centers of the $j$ -th wire segments
$d_{avg}$	-	Average diameter of the planar coil
$d_C$	-	Separation gap between the plates of the capacitor
$D_h$	-	Hydraulic diameter of the microchannel
$d_{in}$	-	Inner diameter of the planar coil

$d_{out}$	-	Outer diameter of the planar coil
$E$	-	Young's modulus of the membrane of the reservoir
$\dot{E}$	-	Thermal power supplied to the air chamber
$f_m$	-	Magnetic field frequency
$f_o$	-	Operating frequency
$F_{P-}$	-	Force generated by the piezoelectric actuator and the coupled parts during negative parts of the voltage signal
$F_{P+}$	-	Force generated by the piezoelectric actuator and the coupled parts during positive parts of the voltage signal
$F_{P0}$	-	Force exerted by the piezoelectric actuator and the coupled parts when no voltage is applied
$F_R$	-	Force exerted by the reservoir
$f_r$	-	Resonant frequency
$f_{rP}$	-	Resonant frequency of the unloaded piezoelectric actuator
$f'_{rP}$	-	Resonant frequency of the loaded piezoelectric actuator
$g^{-1}$	-	Time-shift operator
$h_{air}$	-	Effective heat transfer coefficient of the walls of the air chamber to the surroundings
$h_{max}$	-	Maximum height of the membrane of the reservoir
$i$	-	Number of the segments of the coil
$i_1$	-	Total current of the device coil
$i_2$	-	Total current of the external coil
$j$	-	Number of segments pairs of the coil
$k$	-	Thermal conductivity
$k'$	-	Stiffness of the piezoelectric actuator and coupled PDMS layers
$K_1$	-	Layout dependent constant 1
$K_2$	-	Layout dependent constant 2
$k_B$	-	Boltzmann constant
$L$	-	Inductor
$l$	-	Length of the coil
$L_1$	-	Inductance of the external coil
$L_2$	-	Inductance of the device coil

$l_2$	-	Total length of the device coil
$l_{2,i}$	-	Length of the $i$ -th wire segment of the device coil
$L_{2,i}$	-	Self-inductance value of each wire segment of the device coil
$l_C$	-	Length of the microchannel
$L_{Co}$	-	Inductance of the coil
$L_{S1}$	-	Self-inductance of the device coil
$L_{S2}$	-	Self-inductance of the external coil
$L_T$	-	Total inductance measured when the two coils are connected in series
$m$	-	Effective mass of the unloaded piezoelectric actuator
$M$	-	Mutual inductance between two coils
$m'$	-	Effective mass of the piezoelectric actuator and coupled PDMS layers
$M_{2,j}$	-	Mutual inductance of between each pair of wire segments of the device coil
$N$	-	Number of air molecules enclosed in the air chamber.
$n$	-	Number of turns
$ni$	-	point inside the microchannel
$n_p$	-	Total number of sample points inside the cross-section of the microchannel
$P$	-	Power consumed in the heater
$p$	-	Pressure
$Pe$	-	Peclet number
$Q$	-	conduction of energy transfer
$q$	-	Flow rate
$r$	-	Radius of the microchannel
$R$	-	Resistance of the coil
$r_1$	-	Bare radius of the wire of the external coil
$R_1$	-	Resistance of the external coil
$r_2$	-	Bare radius of the wire of the device coil
$R_2$	-	Resistance of the device coil
$r_C$	-	Diagonal length of the microchannel.
$R_C$	-	Radial location in the microchannel
$Re$	-	Reynolds number

$R_P$	-	Resistance of the piezoelectric actuator
$R_s$	-	Internal resistance of the voltage source
$R_T$	-	Thermal resistance to the surroundings
$s$	-	Deformation of the walls
$s_C$	-	Separation gap of the planar coil
$s_T$	-	Total displacement of the piezoelectric actuator
$T$	-	Absolute temperature
$t$	-	Time
$T_0$	-	Room temperature
$T_1$	-	New temperature
$T_{SS}$	-	Steady state temperature generated in the heater
$u$	-	Flow velocity
$u_z$	-	$z$ -component of the flow velocity
$v$	-	Electromotive force
$V$	-	Volume of the gas
$V_0$	-	Volume of the air in the chamber at room temperature
$V_1$	-	Volume of the air in the chamber at new temperature
$V_D$	-	Dispensed liquid volume
$v_P$	-	Voltage across the piezoelectric actuator
$V_{PBS}$	-	Volumes of the PBS solution
$V_R$	-	Volume of the reservoir
$v_S$	-	Voltage source
$V_T$	-	Total volume of the PBS and pH 4 buffer solutions
$w_C$	-	Width of the planar coil
$Z_1$	-	Total impedance of the device coil
$Z_2$	-	Total impedance of the external coil
$\alpha$	-	Parameter that control the shape and the amplitude of the hysteresis loop
$\alpha_R$	-	Temperature coefficient of the resistance of the circuit
$\beta$	-	Parameter that control the shape and the amplitude of the hysteresis loop
$\gamma$	-	Parameter that control the shape and the amplitude of the hysteresis loop

$\delta$	-	Skin depth of the conductor
$\Delta h$	-	Change in the height of the membrane of the reservoir
$\Delta p$	-	Change in pressure inside the air chamber
$\Delta T$	-	Temperature difference between the heater and the chamber
$\Delta V$	-	Volume difference of the air in the chamber
$\Delta x$	-	Thickness of the membrane of the reservoir
$\Delta xy$	-	Gap separation distance
$\epsilon_0$	-	Vacuum permittivity
$\epsilon_r$	-	Dielectric constant of the dielectric material
$\mu$	-	Absolute magnetic permeability
$\mu_0$	-	Magnetivity of free space
$\rho$	-	Resistivity of the material
$\rho_f$	-	Fluid density
$\rho_{fr}$	-	Fill ratio
$\sigma$	-	Standard deviation of the molar concentration across the channel
$\sigma_M$	-	Standard deviation of the distance travelled by a molecule
$\sigma_{max}$	-	Maximum standard deviation at the inlet of the main microchannel
$\omega$	-	Angular frequency of the AC current
$\Omega$	-	Ohm

**LIST OF APPENDICES**

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
APPENDIX A	Figure 2.4 Reuse Permission	146



## CHAPTER 1

### INTRODUCTION

#### 1.1 Introduction

Microelectromechanical systems (MEMS) is a promising technology that has enabled various sensors [1], actuators [2], electronics [3], and structures [4] to be realized. This consequently enabled manufacturing a wide range of miniaturized devices using microfabrication techniques [5]. Since the beginning of MEMS development, fluidic devices have captured the attention of researchers, which made them among the first devices to be fabricated in microscale [6]. The rapid development of MEMS-compatible technologies has provided means to continuously develop and miniaturize microfluidic devices, which allowed them to precisely manipulate small volumes of liquids within a short time. In addition, such devices require less human intervention and a lower cost, while maintaining a higher sensitivity and stability when compared to traditional fluidic platforms [7]. Since then, several types of microfluidic devices have been developed, such as micropumps [8], micromixers [9], microvalves [10], microneedles [11], microreservoirs [12], and microchannels [13]. However, the first three types form the majority of the reported microfluidic devices, due to their crucial functions in modern-day microfluidic applications [14-16].

In numerous microfluidic systems, a self-contained micropump is an essential component for precise samples/reagents transport, metering, and delivery [14]. Therefore, micropumping components are often integrated into such systems to achieve a reasonable flow rate and overcome the induced back pressure [16]. In addition to the micropump, the micromixer is another component that plays a core role

in various microfluidic devices, where rapid homogeneous mixing is essential for biological assays and chemical reactions [17]. In such devices, mixing is dominated by a slow molecular diffusion, which is caused by the laminar flow that occurs at low Reynolds number ( $Re$ ) values [18]. Thus, micromixers are utilized to overcome this challenge within microscale geometries, where traditional methods of stirring fluids are inapplicable [19]. The microvalve is another substantial component in microfluidic devices, which performs sealing, isolating regions, containing reagents, on/off switching, and regulating the fluids flow [20, 21].

Several types of micropumps, micromixers, and microvalves have been developed to achieve the aforementioned tasks using different approaches that suit the desired applications. These devices are often operated using different types of microactuators, such as electrostatic [22], electromagnetic [23], shape memory alloy (SMA) [24], thermal [25], piezoelectric [26], and thermopneumatic microactuators [27]. Electrostatic microactuators provide fast response and high efficiency. However, they have a short lifetime and require a high driving voltage while generating small stroke [28]. Despite the high efficiency possessed by electromagnetic microactuators, they suffer from limitations in terms of process and material compatibility, and the integration of the magnetic material into the overall fabrication process [29]. SMA microactuators offer a high force and a large actuation range. However, they are similar to thermal microactuators in terms of having low efficiency and slow cycle rates [30]. Piezoelectric actuators (PEAs) have the highest efficiency among the other types of microactuators. Furthermore, they have the advantages of high resolution in the nanometer range, fast response, and high stiffness [31]. Thermopneumatic microactuators are well-known for generating large pressure and deflection with a relatively low input voltage [5]. Thus, piezoelectric and thermopneumatic microactuators are favorable choices in various microfluidic applications.

The aforementioned attractive characteristics of microfluidic devices and their various actuation mechanisms promoted the integration of transport [32], mixing [33], separation [34], regulation [35], analyzing [36], and delivery [37] of biomedical samples into a single microfluidic device. The integration of some or all of the aforementioned operations led to the development of several biomedical applications,

such as gene detection [38], cell culture [39], medical imaging [40], drug delivery [41], lab-on-a-chip (LOC) [42], point-of-care (POC) diagnostics [43], and micro total analysis systems ( $\mu$ TAS) [44]. Nevertheless, there are still opportunities for further enhancements in terms of the design, fabrication, and powering approaches of microfluidic devices in order to enhance their performance and implementation in portable and implantable applications.

## 1.2 Problem Statement

Despite the vast amount of research reported on micropumps, micromixers, and microvalves, the ability to miniaturize and implement these devices in portable and implantable applications is still limited. There are still many challenges with their actuation, powering, and integration methods. To date, such devices are restricted to the use of bulky magnetic cores [45], biofuel cells [46], nuclear cells [47], or on-board batteries [48]. These approaches are not suitable for long-term operation implants and require consideration of several practical issues, such as the device size and power stability, as well as the feasibility for biomedical applications and multiple-actuator control. Passively operated actuators offer the opportunity to minimize the size and cost of such systems while maintaining a higher robustness and longevity as compared to actively operated actuators. Additionally, passively operated systems are more favorable in the field of implantable biomedical devices, since they offer less potential risk and a longer interval between replacement surgeries, and require less complicated procedures when it comes to manufacturing and sealing with biocompatible materials [49]. Wireless actuation methods can potentially address the aforementioned issues in implantable microfluidic devices. One possible wireless actuation method can be achieved using wireless inductor-capacitor (LC) resonant circuits that are controlled by external magnetic fields. These LC circuits can be either designed to pass the transferred power to a microactuator or utilize that power to generate Joule heating and form passive heaters [50-54]. However, wireless actuation methods in microfluidic devices have not been well-explored. There still exist areas for continued development in terms of microactuation mechanisms and multiple-microactuator control. Addressing these issues will allow selective-activating of multiple

microactuators to be realized, which will consequently allow multiple-drug delivery at different doses and concentrations for several clinical applications, such as treatments for Parkinson's disease, diabetes, and glaucoma [50]. Furthermore, these abilities will also allow developing and testing multiple drugs in a single implantation using one animal [55].

Other issues associated with microfluidic devices are the fabrication process and microactuators integration in these devices, which usually consist of several steps that require high-cost fabrication methods [56]. Nonetheless, several alternative low-cost fabrication methods have been reported to address these issues [57-60]. However, this area has not been well-exploited to achieve a satisfactory advancement. There is still room for improvement in terms of the methods and materials used in molds and structures fabrication, as well as bonding and characterization techniques. These issues can be potentially solved using out-of-clean-room fabrication techniques, which offer cost-effective solutions for batch-fabrication processes.

Addressing the aforementioned challenges associated with microfluidic devices using wireless actuation methods and out-of-clean-room fabrication techniques will promote advances in several biomedical application areas.

### **1.3 Research Objectives**

The main objectives of this research are to develop passive microfluidic devices for biomedical applications that involve a thermopneumatic micropump, a zigzag micromixer, and a piezo-actuated microvalve that are powered and controlled wirelessly using an external magnetic field. The specific objectives are:

1. To determine the parameters that govern the flow in microfluidic devices, as well as their actuation mechanisms and energy sources required.
2. To develop a passive wirelessly-controlled thermopneumatic micropump for drug delivery applications.

3. To develop a wirelessly-controlled passive thermopneumatic zigzag micromixer for variable concentration multi-drug delivery applications.
4. To develop a passive wirelessly-controlled normally-closed piezoelectric microvalve for drug dosage control.
5. To characterize the performance of the developed devices, including their wireless actuation and temporal responses.

#### **1.4 Scope of Research**

The scope of this research focuses on the development of three wirelessly-controlled microfluidic devices for biomedical applications, namely, a thermopneumatic micropump, a passive thermopneumatic zigzag micromixer, and a normally-closed piezoelectric microvalve. Furthermore, this research studies the wireless actuation approaches utilized in thermopneumatic and piezoelectric microactuators, as well as LC circuits design and *in vitro* characterization. In addition, using finite element analysis (FEA), the thermal responses of the LC heaters and thermomechanical behavior of the thermopneumatic microactuators were simulated. Furthermore, the wireless power transfer (WPT) process, piezoelectric microactuation, valving performance, back pressure, and flow and mixing rates were also simulated.

In terms of the fabrication process, this study follows the standard and unconventional of MEMS fabrication techniques, including photolithography, etching, electroplating, three-dimensional (3D) printing, and xurography. The software used in the design were AutoCAD and SolidWorks, while COMSOL Multiphysics<sup>®</sup> was used in the finite element simulation. In addition, the image processing and portions of the simulation were carried out using MATLAB<sup>®</sup>. For the characterization purposes, several instruments, such as a network/spectrum/impedance analyzer, an infrared (IR) thermal camera, a laser displacement sensor, a force sensor, a pH meter, and a microscope were used for the circuits components measurements, thermal analysis,

displacement sensing, force measurement, dispensed liquid volume, and microscopic imaging and flow and mixing rates, respectively.

## 1.5 Research Contributions

The research proposes three significant contributions by utilizing out-of-clean-room fabrication methods to develop three different wirelessly-controlled microfluidic devices that utilize two actuation methods. These contributions can be highlighted as follows:

1. Development of three novel designs with self-contained fluids reservoirs for three microfluidic devices, namely, a thermopneumatic micropump, a thermopneumatic micromixer, and a piezoelectric microvalve.
2. Development of a novel wirelessly-controlled thermopneumatic micropump that is operated using a passive frequency-sensitive wireless planar LC heater enabled by an external magnetic field. The device can pump the liquid stored in its reservoir using single or multiple strokes without requiring moving parts.
3. Development of a novel wirelessly-controlled passive zigzag thermopneumatic micromixer by selectively activating two passive wireless planar LC heaters enabled by an external magnetic field. The micromixer provides mixing-ratio controllability in a relatively short mixing length.
4. Development of a novel wirelessly-controlled normally-closed piezoelectric microvalve that is operated by activating a wireless LC resonant circuit using an external magnetic field. The LC circuit was formed by connecting a multilayer coil to a piezoelectric microactuator that behaves as a capacitor and a resistor in parallel. The device efficiently controls the flow of the fluid that is stored in a pressurized balloon reservoir during short and long-term tests.

## **1.6 Potential Impact of the Research**

The applications of MEMS microfluidic implantable medical devices are very limited, due to the limitation of mobility of these devices when using wires and conventional powering methods. To date, the alternative solutions of this problem are using on-board batteries, magnets, biofuel cells, or nuclear cells, which increase the size of these devices and limit their application range and operation time [47]. The use of the proposed wirelessly-controlled micropump, micromixer, and microvalve can uniquely address these limitations and allows developing their implementation in a variety of potential applications. One of these promising applications is implantable drug delivery devices, where the powering method, biocompatibility, and overall size are very crucial factors to ensure achieving minimal invasiveness and long-term operation [49]. In addition, the ability to wirelessly-control multiple microactuators that are integrated into a single device in a selective manner will play an important role in microfluidic devices for multiple-drug delivery [55] and multifunctional systems [25]. Furthermore, the ability to utilize a piezoelectric microactuator to serve as a capacitor and a microactuator simultaneously will eliminate the need for an additional capacitor to form the LC circuit. This can greatly reduce the size, cost and fabrication complexity of wireless devices that contain piezoelectric microactuators or other types of microactuators, such as dielectric elastomers [61]. Moreover, the out-of-clean-room fabrication methods utilized in this thesis offer promising alternative fast, reliable, and cost-effective solutions microfluidic devices fabrication, which opens doors to new batch-fabrication processes. The proposed study contributes to multidisciplinary fields and can be utilized in several essential research areas. The successful outcomes of this research are expected to promote advances in these device technologies in biomedical fields and beyond.

## **1.7 Methodology**

In order to achieve the objectives of this research and according to the aforementioned review, the methodology that followed in this work involved multiple steps that were taken to develop three wirelessly-controlled microfluidic devices,

namely, a thermopneumatic micropump, a passive zigzag thermopneumatic micromixer, and a normally-closed piezo-actuated microvalve. The development process of these devices involves the design, simulation, fabrication, and characterization. The dimensions, materials, operating frequencies, and fabrication methods of the developed devices were selected to be within the range of the reported implantable and portable microfluidic devices [6, 20, 30, 31, 51, 62-73]. It is worth mentioning that miniaturizing certain parts of the developed devices, such as the microchannels and the LC circuits was constrained by limitation of the utilized fabrication methods. The aforementioned steps are further explained in the following subsections.

#### **i. Design and Simulation of the Wireless Thermopneumatic Micropump**

In this stage, a literature review on micropumps and their actuation mechanisms has been performed, where thermopneumatic micropumps and the parameters that affect their design, actuation, and performance were the main focus. In addition, this review involved the methods and challenges related to the wireless control of passive heaters. COMSOL Multiphysics<sup>®</sup> software was utilized to perform the FEA on the wireless thermopneumatic micropump. The design of the device, thickness of the PDMS walls, and the pumping performance were analyzed at this stage.

#### **ii. Fabrication and Characterization of the Wireless Thermopneumatic Micropump**

Based on the FEA results, the passive wireless heater of the device was fabricated by following MEMS fabrication process, which includes photolithography and wet etching, while the structure of the micropump was fabricated using PDMS replication with 3D printed molds. The experimental temporal thermomechanical and pumping results were compared with the simulation results.



### **iii. Design and Simulation of the Wireless Passive Zigzag Thermopneumatic Micromixer**

A literature review on micromixers and their mixing mechanisms has been carried out, where passive zigzag micromixers and their design parameters were the main concern. Integration and selective activation of multiple passive heaters with different  $f_r$  were necessary to realize this micromixer. COMSOL Multiphysics® software was utilized to perform the FEA on the wireless thermopneumatic passive zigzag micromixer to analyze the design of the device, thickness of the PDMS walls, and the mixing and pumping performances.

### **iv. Fabrication and Characterization of the Wireless Passive Zigzag Thermopneumatic Micromixer**

Two passive wireless heaters were fabricated according to the simulation results and by following the same steps used to fabricate the passive heater of the thermopneumatic micropump, while the structure of the micromixer was fabricated using photolithography process. In addition, the temporal thermomechanical, pumping and mixing performances were characterized and compared with the simulation results.

### **v. Design and Simulation of the Wireless Normally-Closed Piezo-Actuated Microvalve**

In this step, a literature review on microvalves and their actuation mechanisms has been performed, where piezo-actuated normally closed microvalves and the parameters that affect their design, actuation, and performance were the main topic. In addition, this review also involved the methods and challenges of achieving the wireless control of piezoelectric actuators, as well as the design factors of pressurized microreservoirs. COMSOL Multiphysics® software was utilized to perform the FEA on the device to analyze the design, thickness of the PDMS microreservoirs and walls, and the valving performance.


**vi. Fabrication and Characterization of Wireless Normally-Closed Piezo-Actuated Microvalve**

The structure of the device was fabricated according to the FEA results using xurography fabrication process while encapsulating a piezoelectric microactuator within the structure of the device. Furthermore, the experimental temporal pressure of the microreservoirs, piezoelectric actuation, and valving performance were compared with the simulation results.

**vii. Optimization and Application**

The optimization process of the developed devices focuses mainly on the improvement of the temporal response, design, characterization, and fabrication related issues. The improvement of the temporal response includes using optimal  $f_r$  values, and LC circuits and microchannels designs to achieve optimal pumping, mixing, and valving performances. Potential applications of the developed devices were presented and detailed analysis were performed.

The aforementioned steps are summarized in Figure 1.1, which shows a flowchart of the general methodology steps followed in this thesis.



**Figure 1.1:** General methodology steps followed in this thesis

## 1.8 Thesis Outline

This thesis is divided into six chapters. Chapter 1 is a general overview of MEMS microfluidic devices and their main types and applications, followed by the problem statement, objectives, scope, and methodology of the research. Chapter 2 presents the literature review of this research, which covers an overview of the categories of MEMS micropumps, micromixers, and microvalves, followed by their actuation mechanisms, including thermopneumatic and piezoelectric actuations, as well as their powering methods, including wireless WPT. Chapter 3 presents a novel thermopneumatic micropump and studies the wireless control of a single passive planar LC heater that drives a thermopneumatic actuator, and the thermomechanical behavior and pumping performance of the device. Chapter 4 proposes a novel wireless passive zigzag thermopneumatic micromixer that is operated wirelessly using two passive planar LC heaters, and demonstrates the ability of selective activation of each actuator, as well as the thermomechanical, pumping, and mixing behaviors. Chapter 5 presents a novel wireless normally-closed piezoelectric microvalve and demonstrates the ability to form an LC circuit by connecting a multilayer coil to the piezoelectric microactuator, as well as the wireless valving performance during short and long-term operations. The thesis concludes with Chapter 6, where the key results and directions for future work are discussed, followed by a list of publications arising from the thesis.

## REFERENCES

1. Toledo, J., Ruiz-Díez, V., Pfusterschmied, G., Schmid, U. and Sánchez-Rojas, J. L. Flow-through Sensor Based on Piezoelectric MEMS Resonator for the in-Line Monitoring of Wine Fermentation. *Sensors and Actuators B: Chemical*. 2018. 254: 291-298.
2. Uvarov, I. V., Lokhanin, M. V., Postnikov, A. V., Melenev, A. E. and Svetovoy, V. B. Electrochemical Membrane Microactuator with a Millisecond Response Time. *Sensors and Actuators B: Chemical*. 2018. 260: 12-20.
3. Zong, X. and Zhu, R. ZnO Nanorod-Based FET Biosensor for Continuous Glucose Monitoring. *Sensors and Actuators B: Chemical*. 2018. 255: 2448-2453.
4. Teranishi, M., Chen, C.-Y., Chang, T.-F. M., Konishi, T., Yamane, D., Machida, K., Masu, K. and Sone, M. Enhancement in Structure Stability of Gold Micro-Cantilever by Constrained Fixed-End in MEMS Devices. *Microelectronic Engineering*. 2018. 187-188: 105-109.
5. Sanjay, S. T., Zhou, W., Dou, M., Tavakoli, H., Ma, L., Xu, F. and Li, X. Recent Advances of Controlled Drug Delivery Using Microfluidic Platforms. *Advanced Drug Delivery Reviews*. 2017. (In press).
6. Nguyen, N.-T., Huang, X. and Chuan, T. K. MEMS-Micropumps: A Review. *Journal of Fluids Engineering*. 2002. 124(2): 384-392.
7. Chiou, C. H., Yeh, T. Y. and Lin, J. L. Deformation Analysis of a Pneumatically-Activated Polydimethylsiloxane (PDMS) Membrane and Potential Micro-Pump Applications. *Micromachines*. 2015. 6(2): 216-229.
8. Gerasimenko, T. N., Kindeeva, O. V., Petrov, V. A., Khaustov, A. I. and Trushkin, E. V. Modelling and Characterization of a Pneumatically Actuated Peristaltic Micropump. *Applied mathematical modelling*. 2017. 52: 590-602.
9. Hermann, P., Timmermann, J., Hoffmann, M., Schlüter, M., Hofmann, C., Löb, P. and Ziegenbalg, D. Optimization of a Split and Recombine Micromixer

- by Improved Exploitation of Secondary Flows. *Chemical Engineering Journal*. 2018. 334: 1996-2003.
10. Ferraro, D., Serra, M., Ferrante, I., Viovy, J. L. and Descroix, S. Microfluidic Valve with Zero Dead Volume and Negligible Back-Flow for Droplets Handling. *Sensors and Actuators B: Chemical*. 2018. 258: 1051-1059.
  11. Wang, Q. L., Zhang, X. P., Chen, B. Z. and Guo, X. D. Dissolvable Layered Microneedles with Core-Shell Structures for Transdermal Drug Delivery. *Materials Science and Engineering: C*. 2018. 83: 143-147.
  12. Gu, Y., Wang, J., Pan, M., Yun, Y., Wen, W., Fang, G. and Wang, S. On-Chip Multiplex Electrochemical Immunosensor Based on Disposable 24-Site Fluidic Micro-Array Screen Printing Analytical Device for Multi-Component Quantitative Analysis. *Sensors and Actuators B: Chemical*. 2018. 260: 499-507.
  13. Vladislavljević, G. T., Ekanem, E. E., Zhang, Z., Khalid, N., Kobayashi, I. and Nakajima, M. Long-Term Stability of Droplet Production by Microchannel (Step) Emulsification in Microfluidic Silicon Chips with Large Number of Terraced Microchannels. *Chemical Engineering Journal*. 2018. 333: 380-391.
  14. Zhang, C., Xing, D. and Li, Y. Micropumps, Microvalves, and Micromixers within Pcr Microfluidic Chips: Advances and Trends. *Biotechnology advances*. 2007. 25(5): 483-514.
  15. Mark, D., Haeberle, S., Roth, G., von Stetten, F. and Zengerle, R. Microfluidic Lab-on-a-Chip Platforms: Requirements, Characteristics and Applications. *Chemical Society reviews*. 2010. 39(3): 1153-1182.
  16. Chen, K. and Hugh Fan, Z. Introduction to Microfluidics. In: Hugh Fan, Z. *Circulating Tumor Cells: Isolation and Analysis*. NJ, USA: John Wiley & Sons, Inc. 33-50; 2016.
  17. Hai Le, T., Bao Quoc, T., Hoa Le, T., Tao, D., Trung Nguyen, T. and Frank, K. Geometric Effects on Mixing Performance in a Novel Passive Micromixer with Trapezoidal-Zigzag Channels. *Journal of Micromechanics and Microengineering*. 2015. 25(9): 094004-094015.
  18. Zhou, M., Bai, D., Zong, Y., Zhao, L. and Thornock, J. N. Numerical Investigation of Turbulent Reactive Mixing in a Novel Coaxial Jet Static Mixer. *Chemical Engineering and Processing: Process Intensification*. 2017. 122: 190-203.

19. Hossain, S. and Kim, K.-Y. Mixing Analysis of Passive Micromixer with Unbalanced Three-Split Rhombic Sub-Channels. *Micromachines*. 2014. 5(4): 913-928.
20. Oh, K. W. and Ahn, C. H. A Review of Microvalves. *Journal of Micromechanics and Microengineering*. 2006. 16(5): R13-R39.
21. Ellinas, K., Tserepi, A. and Gogolides, E. Superhydrophobic, Passive Microvalves with Controllable Opening Threshold: Exploiting Plasma Nanotextured Microfluidics for a Programmable Flow Switchboard. *Microfluidics and nanofluidics*. 2014. 17(3): 489-498.
22. Shirkosh, M., Hojjat, Y. and Sadeghian, H. A New Design of Electrostatic Traveling Wave (ETW) Micropump and the Effect of Parameters on the Flow Rate. *Flow Measurement and Instrumentation*. 2016. 48: 8-14.
23. Wen, M., Kim, C. N. and Yan, Y. Mixing of Two Different Electrolyte Solutions in Electromagnetic Rectangular Mixers. *Journal of Hydrodynamics, Ser. B*. 2016. 28(1): 114-124.
24. Zhang, A.-L., Zhang, X.-Q., Hu, W.-Y. and Fu, X.-T. A Shape Memory Alloy Microvalve Switching Off by Surface Acoustic Wave. *Ferroelectrics*. 2017. 506(1): 1-9.
25. Petrucci, G., Caputo, D., Lovecchio, N., Costantini, F., Legnini, I., Bozzoni, I., Nascetti, A. and de Cesare, G. Multifunctional System-on-Glass for Lab-on-Chip Applications. *Biosensors and Bioelectronics*. 2017. 93: 315-321.
26. Liu, J., Guan, E., Li, P., Wang, F., Liang, C. and Zhao, Y. Deflection Behavior of a Piezo-Driven Flexible Actuator for Vacuum Micropumps. *Sensors and Actuators A: Physical*. 2017. 267: 30-41.
27. Jun, D. H. and Yang, S. S. The Influence of the Geometry of the Pump Chamber on the Characteristics of the Thermopneumatic-Drive Surface Tension Micropump. *Sensors and Actuators A: Physical*. 2015. 234: 294-301.
28. Bell, D., Lu, T., Fleck, N. and Spearing, S. MEMS Actuators and Sensors: Observations on Their Performance and Selection for Purpose. *Journal of Micromechanics and Microengineering*. 2005. 15(7): S153-S164.
29. Pelrine, R., Kornbluh, R., Joseph, J., Heydt, R., Pei, Q. and Chiba, S. High-Field Deformation of Elastomeric Dielectrics for Actuators. *Materials Science and Engineering: C*. 2000. 11(2): 89-100.

30. Iverson, B. D. and Garimella, S. V. Recent Advances in Microscale Pumping Technologies: A Review and Evaluation. *Microfluidics and nanofluidics*. 2008. 5(2): 145-174.
31. Ashraf, M. W., Tayyaba, S. and Afzulpurkar, N. Micro Electromechanical Systems (MEMS) Based Microfluidic Devices for Biomedical Applications. *International journal of molecular sciences*. 2011. 12(6): 3648-3704.
32. Li, X., Liu, S., Fan, P., Werner, C. F., Miyamoto, K.-i. and Yoshinobu, T. A Bubble-Assisted Electroosmotic Micropump for a Delivery of a Droplet in a Microfluidic Channel Combined with a Light-Addressable Potentiometric Sensor. *Sensors and Actuators B: Chemical*. 2017. 248: 993-997.
33. Nam, J. and Lim, C. S. Micromixing Using Swirling Induced by Three-Dimensional Dual Surface Acoustic Waves (3D-dSAW). *Sensors and Actuators B: Chemical*. 2018. 255: 3434-3440.
34. Foroozan Jahromi, P., Karimi-Sabet, J. and Amini, Y. Ion-Pair Extraction-Reaction of Calcium Using Y-Shaped Microfluidic Junctions: An Optimized Separation Approach. *Chemical Engineering Journal*. 2018. 334: 2603-2615.
35. Shaegh, S. A. M., Pourmand, A., Nabavinia, M., Avcı, H., Tamayol, A., Mostafalu, P., Ghavifekr, H. B., Aghdam, E. N., Dokmeci, M. R., Khademhosseini, A. and Zhang, Y. S. Rapid Prototyping of Whole-Thermoplastic Microfluidics with Built-in Microvalves Using Laser Ablation and Thermal Fusion Bonding. *Sensors and Actuators B: Chemical*. 2018. 255: 100-109.
36. Ge, A., Hu, L., Wang, X., Zhu, J., Feng, X., Du, W. and Liu, B.-F. Logarithmic Bacterial Gradient Chip for Analyzing the Effects of Dietary Restriction on *C. Elegans* Growth. *Sensors and Actuators B: Chemical*. 2018. 255: 735-744.
37. Sundararajan, P., Wang, J., Rosen, L. A., Procopio, A. and Rosenberg, K. Engineering Polymeric Janus Particles for Drug Delivery Using Microfluidic Solvent Dissolution Approach. *Chemical engineering science*. 2018. 178: 199-210.
38. Yu, J.-C., Hu, C.-C., Chang, W.-H., Chen, P.-C., Lee, M. S., Peng, K.-T. and Lee, G.-B. An Integrated Microfluidic System Using Mannose-Binding Lectin for Bacteria Isolation and Biofilm-Related Gene Detection. *Microfluidics and nanofluidics*. 2018. 22(1): 13-22.



39. Huang, Y.-X., He, C.-L., Wang, P., Pan, Y.-T., Tuo, W.-W. and Yao, C.-C. Versatile on-Stage Microfluidic System for Long Term Cell Culture, Micromanipulation and Time Lapse Assays. *Biosensors and Bioelectronics*. 2018. 101: 66-74.
40. Huang, L., Zhao, P., Wu, J., Chuang, H.-S. and Wang, W. On-Demand Dielectrophoretic Immobilization and High-Resolution Imaging of *C. Elegans* in Microfluids. *Sensors and Actuators B: Chemical*. 2018. 259: 703-708.
41. Bokharaei, M., Saatchi, K. and Häfeli, U. O. A Single Microfluidic Chip with Dual Surface Properties for Protein Drug Delivery. *International journal of pharmaceutics*. 2017. 521(1): 84-91.
42. Kong, X., Chong, X., Squire, K. and Wang, A. X. Microfluidic Diatomite Analytical Devices for Illicit Drug Sensing with Ppb-Level Sensitivity. *Sensors and Actuators B: Chemical*. 2018. 259: 587-595.
43. Bose, I., Ohlander, A., Kutter, C. and Russom, A. An Integrated All Foil Based Micro Device for Point of Care Diagnostic Applications. *Sensors and Actuators B: Chemical*. 2018. 259: 917-925.
44. Sun, Y., Yuan, J., Pang, J., Li, X., Wang, S., Zhou, Y., Xu, F., Li, P. C. H., Jiang, S. and Chen, H. Millifluidic Chip with a Modular Design Used as a Sample Pretreatment Cartridge for Flour and Flour Food Products. *Talanta*. 2018. 179: 719-725.
45. Gusenbauer, M., Mazza, G., Posnicek, T., Brandl, M. and Schrefl, T. Magnetically Actuated Circular Displacement Micropump. *The International Journal of Advanced Manufacturing Technology*. 2017. 1-14.
46. Katz, E. and MacVittie, K. Implanted Biofuel Cells Operating in Vivo - Methods, Applications and Perspectives - Feature Article. *Energy & Environmental Science*. 2013. 6(10): 2791-2803.
47. Ben Amar, A., Kouki, A. B. and Cao, H. Power Approaches for Implantable Medical Devices. *Sensors*. 2015. 15(11): 28889-28914.
48. Vinayakumar, K. B., Nadiger, G., Shetty, V. R., Dinesh, N. S., Nayak, M. M. and Rajanna, K. Packaged Peristaltic Micropump for Controlled Drug Delivery Application. *Review of Scientific Instruments*. 2017. 88(1): 015102-015108.
49. Joung, Y.-H. Development of Implantable Medical Devices: From an Engineering Perspective. *International Neurourology Journal*. 2013. 17(3): 98-106.

50. Mohamed Ali, M. S. and Takahata, K. Wireless Microfluidic Control with Integrated Shape-Memory-Alloy Actuators Operated by Field Frequency Modulation. *Journal of Micromechanics and Microengineering*. 2011. 21(7): 075005-075015.
51. Lee, C. H., Jeong, J.-W., Liu, Y., Zhang, Y., Shi, Y., Kang, S.-K., Kim, J., Kim, J. S., Lee, N. Y., Kim, B. H., Jang, K.-I., Yin, L., Kim, M. K., Banks, A., Paik, U., Huang, Y. and Rogers, J. A. Materials and Wireless Microfluidic Systems for Electronics Capable of Chemical Dissolution on Demand. *Advanced functional materials*. 2015. 25(9): 1338-1343.
52. Lee, C. H., Kim, H., Harburg, D. V., Park, G., Ma, Y., Pan, T., Kim, J. S., Lee, N. Y., Kim, B. H., Jang, K.-I., Kang, S.-K., Huang, Y., Kim, J., Lee, K.-M., Leal, C. and Rogers, J. A. Biological Lipid Membranes for on-Demand, Wireless Drug Delivery from Thin, Bioresorbable Electronic Implants. *NPG Asia materials*. 2015. 7: e227-e294.
53. Cobo, A., Sheybani, R., Tu, H. and Meng, E. A Wireless Implantable Micropump for Chronic Drug Infusion against Cancer. *Sensors and actuators. A, Physical*. 2016. 239: 18-25.
54. Noh, K. N., Park, S. I., Qazi, R., Zou, Z., Mickle, A. D., Grajales-Reyes, J. G., Jang, K.-I., Gereau, R. W., Xiao, J., Rogers, J. A. and Jeong, J.-W. Miniaturized, Battery-Free Optofluidic Systems with Potential for Wireless Pharmacology and Optogenetics. *Small (Weinheim an der Bergstrasse, Germany)*. 2017. 14: 1702479-1702486.
55. Shin, H., Lee, H. J., Chae, U., Kim, H., Kim, J., Choi, N., Woo, J., Cho, Y., Lee, C. J., Yoon, E.-S. and Cho, I.-J. Neural Probes with Multi-Drug Delivery Capability. *Lab on a chip*. 2015. 15(18): 3730-3737.
56. Walsh, D. I., Kong, D. S., Murthy, S. K. and Carr, P. A. Enabling Microfluidics: From Clean Rooms to Makerspaces. *Trends in biotechnology*. 2017. 35(5): 383-392.
57. Zhao, S., Cong, H. and Pan, T. Direct Projection on Dry-Film Photoresist (DP2): Do-It-Yourself Three-Dimensional Polymer Microfluidics. *Lab on a chip*. 2009. 9(8): 1128-1132.
58. Shaun, P. G., Terrence, M. M., Jr. and Tingrui, P. Print-to-Pattern Dry Film Photoresist Lithography. *Journal of Micromechanics and Microengineering*. 2014. 24(5): 057002-057018.

59. Kakoti, A., Siddiqui, M. F. and Goswami, P. A Low Cost Design and Fabrication Method for Developing a Leak Proof Paper Based Microfluidic Device with Customized Test Zone. *Biomicrofluidics*. 2015. 9(2): 026502-026512.
60. Tsao, C.-W. Polymer Microfluidics: Simple, Low-Cost Fabrication Process Bridging Academic Lab Research to Commercialized Production. *Micromachines*. 2016. 7(12): 225-235.
61. Mohd Ghazali, F. A., Mah, C. K., AbuZaiter, A., Chee, P. S. and Mohamed Ali, M. S. Soft Dielectric Elastomer Actuator Micropump. *Sensors and Actuators A: Physical*. 2017. 263: 276-284.
62. Laser, D. and Santiago, J. A Review of Micropumps. *Journal of Micromechanics and Microengineering*. 2004. 14(6): R35-R64.
63. Tsai, N.-C. and Sue, C.-Y. Review of MEMS-Based Drug Delivery and Dosing Systems. *Sensors and Actuators A: Physical*. 2007. 134(2): 555-564.
64. Nisar, A., Afzulpurkar, N., Mahaisavariya, B. and Tuantranont, A. MEMS-Based Micropumps in Drug Delivery and Biomedical Applications. *Sensors and Actuators B: Chemical*. 2008. 130(2): 917-942.
65. Nuxoll, E. Biomems in Drug Delivery. *Advanced Drug Delivery Reviews*. 2013. 65(11): 1611-1625.
66. Hessel, V., Löwe, H. and Schönfeld, F. Micromixers—a Review on Passive and Active Mixing Principles. *Chemical engineering science*. 2005. 60(8): 2479-2501.
67. Nam-Trung, N. and Zhigang, W. Micromixers—a Review. *Journal of Micromechanics and Microengineering*. 2005. 15(2): R1-R16.
68. Suh, Y. K. and Kang, S. A Review on Mixing in Microfluidics. *Micromachines*. 2010. 1(3): 82-111.
69. Lee, C.-Y., Chang, C.-L., Wang, Y.-N. and Fu, L.-M. Microfluidic Mixing: A Review. *International journal of molecular sciences*. 2011. 12(5): 3263-3287.
70. Li, X., Chang, H., Liu, X., Ye, F. and Yuan, W. A 3-D Overbridge-Shaped Micromixer for Fast Mixing over a Wide Range of Reynolds Numbers. *Journal of Microelectromechanical Systems*. 2015. 24(5): 1391-1399.
71. Lee, C.-Y., Wang, W.-T., Liu, C.-C. and Fu, L.-M. Passive Mixers in Microfluidic Systems: A Review. *Chemical Engineering Journal*. 2016. 288: 146-160.

72. Cai, G., Xue, L., Zhang, H. and Lin, J. A Review on Micromixers. *Micromachines*. 2017. 8(9): 274-300.
73. Kim, A., Ochoa, M., Rahimi, R. and Ziaie, B. New and Emerging Energy Sources for Implantable Wireless Microdevices. *IEEE Access*. 2015. 3: 89-98.
74. Nguyen, N.-T. and Wereley, S. T. *Fundamentals and Applications of Microfluidics*. MA, USA: Artech House. 2002.
75. Whitesides, G. M. The Origins and the Future of Microfluidics. *Nature*. 2006. 442: 368-373.
76. Terry, S. C., Jerman, J. H. and Angell, J. B. A Gas Chromatographic Air Analyzer Fabricated on a Silicon Wafer. *IEEE transactions on electron devices*. 1979. 26(12): 1880-1886.
77. van Lintel, H. T. G., van De Pol, F. C. M. and Bouwstra, S. A Piezoelectric Micropump Based on Micromachining of Silicon. *Sensors and Actuators*. 1988. 15(2): 153-167.
78. Smits, J. G. Piezoelectric Micropump with Microvalves. *Proceedings., Eighth University/Government/Industry Microelectronics Symposium*. 12-14 June, 1989. IEEE. 1989. 92-94.
79. Manz, A., Graber, N. and Widmer, H. M. Miniaturized Total Chemical Analysis Systems: A Novel Concept for Chemical Sensing. *Sensors and Actuators B: Chemical*. 1990. 1(1): 244-248.
80. Folch, A. *Introduction to Biomems*. FL, USA: CRC Press. 2016.
81. Novotný, J. and Foret, F. Fluid Manipulation on the Micro-Scale: Basics of Fluid Behavior in Microfluidics. *Journal of separation science*. 2017. 40(1): 383-394.
82. Abgrall, P. and Nguyen, N.-T. *Nanofluidics*. MA, USA: Artech House. 2009.
83. Nguyen, N.-T. *Micromixers: Fundamentals, Design and Fabrication*. 2nd ed. Oxford, UK: William Andrew. 2012.
84. Capretto, L., Cheng, W., Hill, M. and Zhang, X. Micromixing within Microfluidic Devices. In: Lin, B. *Microfluidics: Technologies and Applications*. Berlin, Heidelberg: Springer Berlin Heidelberg. 27-68; 2011.
85. Lee, C.-Y. and Fu, L.-M. Recent Advances and Applications of Micromixers. *Sensors and Actuators B: Chemical*. 2018. 259: 677-702.

86. Chakraborty, D. and Chakraborty, S. Microfluidic Transport and Micro-Scale Flow Physics: An Overview. In: Chakraborty, S. *Microfluidics and Microfabrication*. Boston, MA: Springer US. 1-85; 2010.
87. Ducrée, J., Koltay, P. and Zengerle, R. Microfluidics. In: Korvink, J. and Paul, O. *MEMS: A Practical Guide of Design, Analysis, and Applications*. NY, USA: Springer Science & Business Media. 667-727; 2010.
88. Charmet, J., Arosio, P. and Knowles, T. P. J. Microfluidics for Protein Biophysics. *Journal of molecular biology*. 2017. (In press).
89. Li, Y., Van Roy, W., Lagae, L. and Vereecken, P. M. Analysis of Fully on-Chip Microfluidic Electrochemical Systems under Laminar Flow. *Electrochimica acta*. 2017. 231: 200-208.
90. Raza, W., Hossain, S. and Kim, K.-Y. Effective Mixing in a Short Serpentine Split-and-Recombination Micromixer. *Sensors and Actuators B: Chemical*. 2018. 258: 381-392.
91. Yang, A.-S., Chuang, F.-C., Chen, C.-K., Lee, M.-H., Chen, S.-W., Su, T.-L. and Yang, Y.-C. A High-Performance Micromixer Using Three-Dimensional Tesla Structures for Bio-Applications. *Chemical Engineering Journal*. 2015. 263: 444-451.
92. Tølbøl Sørensen, K. and Kristensen, A. Label-Free Monitoring of Diffusion in Microfluidics. *Micromachines*. 2017. 8(11): 329-335.
93. Das, T. and Chakraborty, S. Bio-Microfluidics: Overview. In: Chakraborty, S. *Microfluidics and Microfabrication*. NY, USA: Springer US. 131-179; 2010.
94. Maluf, N. and Williams, K. *An Introduction to Microelectromechanical Systems Engineering*. London, UK: Artech House. 2004.
95. Senturia, S. D. *Microsystem Design*. Dordrecht, Netherlands: Springer. 2001.
96. Zeng, Y., Shin, M. and Wang, T. Programmable Active Droplet Generation Enabled by Integrated Pneumatic Micropumps. *Lab on a chip*. 2013. 13(2): 267-273.
97. Ashraf, M. W., Tayyaba, S., Nisar, A., Afzulpurkar, N., Bodhale, D. W., Lomas, T., Poyai, A. and Tuantranont, A. Design, Fabrication and Analysis of Silicon Hollow Microneedles for Transdermal Drug Delivery System for Treatment of Hemodynamic Dysfunctions. *Cardiovascular Engineering*. 2010. 10(3): 91-108.

98. Pararas, E. E. L., Borkholder, D. A. and Borenstein, J. T. Microsystems Technologies for Drug Delivery to the Inner Ear. *Advanced Drug Delivery Reviews*. 2012. 64(14): 1650-1660.
99. Ochoa, M., Mousoulis, C. and Ziaie, B. Polymeric Microdevices for Transdermal and Subcutaneous Drug Delivery. *Advanced Drug Delivery Reviews*. 2012. 64(14): 1603-1616.
100. Chappel, E., Allendes, R., Bianchi, F., Calcaterra, G., Cannehan, F., Conan, C., Lefrique, J., Lettieri, G. L., Mefti, S., Noth, A., Proennecke, S. and Neftel, F. Industrialized Functional Test for Insulin Micropumps. *Procedia Engineering*. 2011. 25: 795-798.
101. Hintermüller, M. A., Jakoby, B. and Reichel, E. K. Acoustic Streaming Via a Flexible Pcb for Micropumping Applications. *Procedia Engineering*. 2016. 168: 856-859.
102. Huang, C. and Tsou, C. The Implementation of a Thermal Bubble Actuated Microfluidic Chip with Microvalve, Micropump and Micromixer. *Sensors and Actuators A: Physical*. 2014. 210: 147-156.
103. Kim, S. H., Hashi, S. and Ishiyama, K. Centrifugal Force Based Magnetic Micro-Pump Driven by Rotating Magnetic Fields. *Journal of Physics: Conference Series*. 2011. 266(1): 012072-012076.
104. Russel, M. K., Selvaganapathy, P. R. and Ching, C. Y. Ion Drag Electrohydrodynamic (Ehd) Micro-Pumps under a Pulsed Voltage. *Journal of electrostatics*. 2016. 82: 48-54.
105. Zhao, G., Jian, Y., Chang, L. and Buren, M. Magnetohydrodynamic Flow of Generalized Maxwell Fluids in a Rectangular Micropump under an Ac Electric Field. *Journal of magnetism and magnetic materials*. 2015. 387: 111-117.
106. Choi, J. P., Kim, K. S., Seo, Y. H. and Kim, B. H. Design and Fabrication of Synthetic Air-Jet Micropump. *International Journal of Precision Engineering and Manufacturing*. 2011. 12(2): 355-360.
107. Kim, B. H., Kim, I. C., Kang, Y. J., Ryu, J. and Lee, S. J. Effect of Phase Shift on Optimal Operation of Serial-Connected Valveless Micropumps. *Sensors and Actuators A: Physical*. 2014. 209(0): 133-139.
108. Tanaka, Y., Fujikawa, T., Kazoe, Y. and Kitamori, T. An Active Valve Incorporated into a Microchip Using a High Strain Electroactive Polymer. *Sensors and Actuators B: Chemical*. 2013. 184(0): 163-169.

109. Merzouki, T., Duval, A. and Ben Zineb, T. Finite Element Analysis of a Shape Memory Alloy Actuator for a Micropump. *Simulation Modelling Practice and Theory*. 2012. 27: 112-126.
110. Patrascu, M., Gonzalo-Ruiz, J., Goedbloed, M., Brongersma, S. H. and Crego-Calama, M. Flexible, Electrostatic Microfluidic Actuators Based on Thin Film Fabrication. *Sensors and Actuators A: Physical*. 2012. 186: 249-256.
111. Nguyen Quang, D., Thien Xuan, D., Phuc Hong, P. and Van Thanh, D. Study of Valveless Electromagnetic Micropump by Volume-of-Fluid and Openfoam. *Japanese journal of applied physics*. 2015. 54(5): 057201-057207.
112. Cazorla, P.-H., Fuchs, O., Cochet, M., Maubert, S., Le Rhun, G., Fouillet, Y. and Defay, E. A Low Voltage Silicon Micro-Pump Based on Piezoelectric Thin Films. *Sensors and Actuators A: Physical*. 2016. 250: 35-39.
113. Thompson, B. J. and Ronaldson, P. T. Drug Delivery to the Ischemic Brain. *Advances in pharmacology (San Diego, Calif.)*. 2014. 71: 165-202.
114. Brzica, H., Abdullahi, W., Ibbotson, K. and Ronaldson, P. T. Role of Transporters in Central Nervous System Drug Delivery and Blood-Brain Barrier Protection: Relevance to Treatment of Stroke. *Journal of Central Nervous System Disease*. 2017. 9: 1179573517693802.
115. Song, W. and Lichtenberg, J. Thermo-Pneumatic, Single-Stroke Micropump. *Journal of Micromechanics and Microengineering*. 2005. 15(8): 1425-1432.
116. Do, V. K., Yamamoto, T., Ukita, Y. and Takamura, Y. Precise Flow Control with Internal Pneumatic Micropump for Highly Sensitive Solid-Phase Extraction Liquid Electrode Plasma. *Sensors and Actuators B: Chemical*. 2015. 221: 1561-1569.
117. Zainal, M., Sahlan, S. and Ali, M. Micromachined Shape-Memory-Alloy Microactuators and Their Application in Biomedical Devices. *Micromachines*. 2015. 6(7): 879-901.
118. Huber, J., Fleck, N. and Ashby, M. The Selection of Mechanical Actuators Based on Performance Indices. *Proceedings of the Royal Society of London. Series A: Mathematical, Physical and Engineering Sciences*. 1997. 453(1965): 2185-2205.
119. Gilbertson, R. G. and Busch, J. D. A Survey of Micro-Actuator Technologies for Future Spacecraft Missions. *Journal of the British Interplanetary Society*. 1996. 49(4): 129-138.

120. Chia, B. T., Liao, H.-H. and Yang, Y.-J. A Novel Thermo-Pneumatic Peristaltic Micropump with Low Temperature Elevation on Working Fluid. *Sensors and Actuators A: Physical*. 2011. 165(1): 86-93.
121. Al-Faqheri, W., Ibrahim, F., Thio, T. H. G., Aeinehvand, M. M., Arof, H. and Madou, M. Development of Novel Passive Check Valves for the Microfluidic CD Platform. *Sensors and Actuators A: Physical*. 2015. 222: 245-254.
122. Yang, Y.-J. and Liao, H.-H. Development and Characterization of Thermopneumatic Peristaltic Micropumps. *Journal of Micromechanics and Microengineering*. 2009. 19(2): 025003-025016.
123. Wong, K. K., Tu, J., Sun, Z. and Dissanayake, D. W. *Methods in Research and Development of Biomedical Devices*. NJ, USA: World Scientific. 2013.
124. Handique, K., Burke, D. T., Mastrangelo, C. H. and Burns, M. A. On-Chip Thermopneumatic Pressure for Discrete Drop Pumping. *Analytical chemistry*. 2001. 73(8): 1831-1838.
125. Yang, L.-J. and Lin, T.-Y. A PDMS-Based Thermo-Pneumatic Micropump with Parylene Inner Walls. *Microelectronic Engineering*. 2011. 88(8): 1894-1897.
126. Yoo, J.-C., La, G.-S., Kang, C. J. and Kim, Y.-S. Microfabricated Polydimethylsiloxane Microfluidic System Including Micropump and Microvalve for Integrated Biosensor. *Current Applied Physics*. 2008. 8(6): 692-695.
127. Jeong, O. C., Park, S. W., Yang, S. S. and Pak, J. J. Fabrication of a Peristaltic PDMS Micropump. *Sensors and Actuators A: Physical*. 2005. 123-124: 453-458.
128. Lei, K., Chen, K.-H. and Chang, Y.-C. Protein Binding Reaction Enhanced by Bi-Directional Flow Driven by on-Chip Thermopneumatic Actuator. *Biomedical microdevices*. 2014. 16(2): 325-332.
129. Cooney, C. G. and Towe, B. C. A Thermopneumatic Dispensing Micropump. *Sensors and Actuators A: Physical*. 2004. 116(3): 519-524.
130. Hamid, N. A., Majlis, B. Y., Yunas, J., Syafeeza, A. R., Wong, Y. C. and Ibrahim, M. A Stack Bonded Thermo-Pneumatic Micro-Pump Utilizing Polyimide Based Actuator Membrane for Biomedical Applications. *Microsystem Technologies*. 2017. 23(9): 4037-4043.



131. Belliveau, N. M., Huft, J., Lin, P. J. C., Chen, S., Leung, A. K. K., Leaver, T. J., Wild, A. W., Lee, J. B., Taylor, R. J., Tam, Y. K., Hansen, C. L. and Cullis, P. R. Microfluidic Synthesis of Highly Potent Limit-Size Lipid Nanoparticles for in Vivo Delivery of Sirna. *Molecular Therapy. Nucleic Acids*. 2012. 1(8): e37-e45.
132. Rajabi, N., Bahnemann, J., Tzeng, T.-N., Platas Barradas, O., Zeng, A.-P. and Müller, J. Lab-on-a-Chip for Cell Perturbation, Lysis, and Efficient Separation of Sub-Cellular Components in a Continuous Flow Mode. *Sensors and Actuators A: Physical*. 2014. 215: 136-143.
133. Maleki, T., Fricke, T., Quesenberry, J., Todd, P. and Leary, J. F. Point-of-Care, Portable Microfluidic Blood Analyzer System. *Microfluidics, BioMEMS, and Medical Microsystems X*. 21 January, 2012. International Society for Optics and Photonics. 2012. 82510C-82510C.
134. Nama, N., Huang, P.-H., Huang, T. J. and Costanzo, F. Investigation of Micromixing by Acoustically Oscillated Sharp-Edges. *Biomicrofluidics*. 2016. 10(2): 024124-024140.
135. Lee, H.-Y. and Voldman, J. Optimizing Micromixer Design for Enhancing Dielectrophoretic Microconcentrator Performance. *Analytical chemistry*. 2007. 79(5): 1833-1839.
136. Jalaal, M., Khorshidi, B. and Esmaeilzadeh, E. Electrohydrodynamic (Ehd) Mixing of Two Miscible Dielectric Liquids. *Chemical Engineering Journal*. 2013. 219: 118-123.
137. Thanjavur Kumar, D., Zhou, Y., Brown, V., Lu, X., Kale, A., Yu, L. and Xuan, X. Electric Field-Induced Instabilities in Ferrofluid Microflows. *Microfluidics and nanofluidics*. 2015. 19(1): 43-52.
138. Lim, C. Y., Lam, Y. C. and Yang, C. Mixing Enhancement in Microfluidic Channel with a Constriction under Periodic Electro-Osmotic Flow. *Biomicrofluidics*. 2010. 4(1): 014101-014118.
139. Nouri, D., Zabihi-Hesari, A. and Passandideh-Fard, M. Rapid Mixing in Micromixers Using Magnetic Field. *Sensors and Actuators A: Physical*. 2017. 255: 79-86.
140. Wang, Y., Zhe, J., Chung, B. T. F. and Dutta, P. A Rapid Magnetic Particle Driven Micromixer. *Microfluidics and nanofluidics*. 2007. 4(5): 375-389.

141. Wang, X., Ma, X., An, L., Kong, X., Xu, Z. and Wang, J. A Pneumatic Micromixer Facilitating Fluid Mixing at a Wide Range Flow Rate for the Preparation of Quantum Dots. *Science China Chemistry*. 2013. 56(6): 799-805.
142. Kunti, G., Bhattacharya, A. and Chakraborty, S. Rapid Mixing with High-Throughput in a Semi-Active Semi-Passive Micromixer. *Electrophoresis*. 2017. 38(9-10): 1310-1317.
143. Dogan, H., Nas, S. and Muradoglu, M. Mixing of Miscible Liquids in Gas-Segmented Serpentine Channels. *International Journal of Multiphase Flow*. 2009. 35(12): 1149-1158.
144. Xia, Q. and Zhong, S. Quantification of Liquid Mixing Enhanced by Alternatively Pulsed Injection in a Confined Jet Configuration. *Journal of Visualization*. 2012. 15(1): 57-66.
145. Buchegger, W., Wagner, C., Lendl, B., Kraft, M. and Vellekoop, M. J. A Highly Uniform Lamination Micromixer with Wedge Shaped Inlet Channels for Time Resolved Infrared Spectroscopy. *Microfluidics and nanofluidics*. 2011. 10(4): 889-897.
146. Ahmed, F. and Kim, K.-Y. Parametric Study of an Electroosmotic Micromixer with Heterogeneous Charged Surface Patches. *Micromachines*. 2017. 8(7): 199-214.
147. Xie, T. and Xu, C. Numerical and Experimental Investigations of Chaotic Mixing Behavior in an Oscillating Feedback Micromixer. *Chemical engineering science*. 2017. 171: 303-317.
148. Xia, H. M., Wan, S. Y. M., Shu, C. and Chew, Y. T. Chaotic Micromixers Using Two-Layer Crossing Channels to Exhibit Fast Mixing at Low Reynolds Numbers. *Lab on a chip*. 2005. 5(7): 748-755.
149. Mubashshir Ahmad, A., Kwang-Yong, K., Khalid, A. and Sun Min, K. A Novel Passive Micromixer Based on Unbalanced Splits and Collisions of Fluid Streams. *Journal of Micromechanics and Microengineering*. 2010. 20(5): 055007-055017.
150. Afzal, A. and Kim, K.-Y. Multi-Objective Optimization of a Passive Micromixer Based on Periodic Variation of Velocity Profile. *Chemical Engineering Communications*. 2015. 202(3): 322-331.

151. Santana, H. S., Silva, J. L. and Taranto, O. P. Numerical Simulation of Mixing and Reaction of *Jatropha Curcas* Oil and Ethanol for Synthesis of Biodiesel in Micromixers. *Chemical engineering science*. 2015. 132: 159-168.
152. Farshchian, B., Amirsadeghi, A., Choi, J., Park, D. S., Kim, N. and Park, S. 3D Nanomolding and Fluid Mixing in Micromixers with Micro-Patterned Microchannel Walls. *Nano Convergence*. 2017. 4(1): 4-13.
153. Hossain, S., Husain, A. and Kim, K.-Y. Optimization of Micromixer with Staggered Herringbone Grooves on Top and Bottom Walls. *Engineering Applications of Computational Fluid Mechanics*. 2011. 5(4): 506-516.
154. Yang, J., Qi, L., Chen, Y. and Ma, H. Design and Fabrication of a Three Dimensional Spiral Micromixer. *Chinese Journal of Chemistry*. 2013. 31(2): 209-214.
155. Liu, K., Yang, Q., Chen, F., Zhao, Y., Meng, X., Shan, C. and Li, Y. Design and Analysis of the Cross-Linked Dual Helical Micromixer for Rapid Mixing at Low Reynolds Numbers. *Microfluidics and nanofluidics*. 2015. 19(1): 169-180.
156. Chen, X. and Li, T. A Novel Passive Micromixer Designed by Applying an Optimization Algorithm to the Zigzag Microchannel. *Chemical Engineering Journal*. 2017. 313: 1406-1414.
157. Wang, L., Ma, S., Wang, X., Bi, H. and Han, X. Mixing Enhancement of a Passive Microfluidic Mixer Containing Triangle Baffles. *Asia-Pacific Journal of Chemical Engineering*. 2014. 9(6): 877-885.
158. Stroock, A. D., Dertinger, S. K. W., Ajdari, A., Mezić, I., Stone, H. A. and Whitesides, G. M. Chaotic Mixer for Microchannels. *Science*. 2002. 295(5555): 647-651.
159. Howell, J. P. B., Mott, D. R., Fertig, S., Kaplan, C. R., Golden, J. P., Oran, E. S. and Ligler, F. S. A Microfluidic Mixer with Grooves Placed on the Top and Bottom of the Channel. *Lab on a chip*. 2005. 5(5): 524-530.
160. Sadegh Cheri, M., Latifi, H., Salehi Moghaddam, M. and Shahraki, H. Simulation and Experimental Investigation of Planar Micromixers with Short-Mixing-Length. *Chemical Engineering Journal*. 2013. 234: 247-255.
161. Sheu, T. S., Chen, S. J. and Chen, J. J. Mixing of a Split and Recombine Micromixer with Tapered Curved Microchannels. *Chemical engineering science*. 2012. 71: 321-332.

162. SadAbadi, H., Packirisamy, M. and Wuthrich, R. High Performance Cascaded PDMS Micromixer Based on Split-and-Recombination Flows for Lab-on-a-Chip Applications. *Rsc Advances*. 2013. 3(20): 7296-7305.
163. Vladimir, V. and Mohammad, N. A Novel Generation of 3D Sar-Based Passive Micromixer: Efficient Mixing and Low Pressure Drop at a Low Reynolds Number. *Journal of Micromechanics and Microengineering*. 2013. 23(5): 055023-055036.
164. Mengeaud, V., Josserand, J. and Girault, H. H. Mixing Processes in a Zigzag Microchannel: Finite Element Simulations and Optical Study. *Analytical chemistry*. 2002. 74(16): 4279-4286.
165. Hossain, S., Ansari, M. A. and Kim, K.-Y. Evaluation of the Mixing Performance of Three Passive Micromixers. *Chemical Engineering Journal*. 2009. 150(2-3): 492-501.
166. Glasgow, I., Lieber, S. and Aubry, N. Parameters Influencing Pulsed Flow Mixing in Microchannels. *Analytical chemistry*. 2004. 76(16): 4825-4832.
167. Afzal, A. and Kim, K.-Y. Convergent-Divergent Micromixer Coupled with Pulsatile Flow. *Sensors and Actuators B: Chemical*. 2015. 211: 198-205.
168. Au, A. K., Lai, H., Utela, B. R. and Folch, A. Microvalves and Micropumps for Biomems. *Micromachines*. 2011. 2(4): 179-220.
169. Frimat, J.-P., Becker, M., Chiang, Y.-Y., Marggraf, U., Janasek, D., Hengstler, J. G., Franzke, J. and West, J. A Microfluidic Array with Cellular Valving for Single Cell Co-Culture. *Lab on a chip*. 2011. 11(2): 231-237.
170. Zhou, Y., Basu, S., Wohlfahrt, K. J., Lee, S. F., Klenerman, D., Laue, E. D. and Seshia, A. A. A Microfluidic Platform for Trapping, Releasing and Super-Resolution Imaging of Single Cells. *Sensors and Actuators B: Chemical*. 2016. 232: 680-691.
171. Richter, C., Sachsenheimer, K., Keller, N., Nargang, T. M., Helmer, D., Kotz, F. and Rapp, B. E. An Individual Addressable and Latchable Actuator Array for Microfluidic Systems. *Microfluidics and nanofluidics*. 2016. 20(9): 130-140.
172. Thoma, F., Goldschmidtböing, F. and Woias, P. A New Concept of a Drug Delivery System with Improved Precision and Patient Safety Features. *Micromachines*. 2014. 6(1): 80-95.

173. Yıldırım, E., Arıkan, M. A. S. and Külah, H. A Normally Closed Electrostatic Parylene Microvalve for Micro Total Analysis Systems. *Sensors and Actuators A: Physical*. 2012. 181: 81-86.
174. Augustine, S., Gu, P., Zheng, X., Nishida, T. and Fan, Z. H. Low-Power Electrically Controlled Thermoelastic Microvalves Integrated in Thermoplastic Microfluidic Devices. *Microfluidics and nanofluidics*. 2015. 19(6): 1385-1394.
175. Lin, S., Wang, W., Ju, X. J., Xie, R. and Chu, L. Y. A Simple Strategy for in Situ Fabrication of a Smart Hydrogel Microvalve within Microchannels for Thermostatic Control. *Lab on a chip*. 2014. 14(15): 26-34.
176. Zainal, M. A., Yunus, Y. M., Rahim, R. A. and Ali, M. S. M. Wireless Valving for Centrifugal Microfluidic Disc. *Journal of Microelectromechanical Systems*. 2017. 26(6): 1327-1334.
177. Gholizadeh, A. and Javanmard, M. Magnetically Actuated Microfluidic Transistors: Miniaturized Micro-Valves Using Magnetorheological Fluids Integrated with Elastomeric Membranes. *Journal of Microelectromechanical Systems*. 2016. 25(5): 922-928.
178. Boustheen, A., Homburg, F. G. A. and Dietzel, A. A Modular Microvalve Suitable for Lab on a Foil: Manufacturing and Assembly Concepts. *Microelectronic Engineering*. 2012. 98: 638-641.
179. Groen, M. S., Brouwer, D. M., Wiegerink, R. J. and Lotters, J. C. Design Considerations for a Micromachined Proportional Control Valve. *Micromachines*. 2012. 3(2): 396-412.
180. Ishida, T., McLaughlin, D., Tanaka, Y. and Omata, T. First-Come-First-Serve Microfluidic Device of Droplets Using Hydrophobic Passive Microvalves. *Sensors and Actuators B: Chemical*. 2018. 254: 1005-1010.
181. Zhang, D. Y., Lv, J. L., Jiang, Y. G., Chen, H. W. and Fu, J. C. A Piezoelectric Microvalve with a Flexure-Hinged Driving Frame and Microfabricated Silicon Sealing Pair. *Mechatronics*. 2014. 24(5): 511-518.
182. Baek, S.-K., Yoon, Y.-K. and Park, J.-H. Wirelessly Actuated Microvalve System Using Induction Heating and Its Thermal Effect on the Microfluidic System. *2011 16th International Solid-State Sensors, Actuators and Microsystems Conference*. 5-9 June 2011. IEEE. 2011. 1304-1307.

183. Kim, S., Lee, J. and Choi, B. 3D Printed Fluidic Valves for Remote Operation Via External Magnetic Field. *International Journal of Precision Engineering and Manufacturing*. 2016. 17(7): 937-942.
184. Christof, M. and Manfred, K. Shape Memory Alloy Microvalves for a Fluidic Control System. *Journal of Micromechanics and Microengineering*. 2014. 24(2): 025001-025011.
185. Das, C. and Payne, F. Design and Characterization of Low Power, Low Dead Volume Electrochemically-Driven Microvalve. *Sensors and Actuators A: Physical*. 2016. 241: 104-112.
186. Bonhoeffer, B., Kwade, A. and Juhnke, M. Impact of Formulation Properties and Process Parameters on the Dispensing and Positioning of Drug Nanosuspensions Using Micro-Valve Technology. *Journal of pharmaceutical sciences*. 2017. 106(4): 1102-1110.
187. Bonhoeffer, B., Boldrini, M., Boiger, G., Kwade, A. and Juhnke, M. Experimental Characterization and Simulation of a Piezo-Actuated Micro Dispensing Valve. *Journal of Fluids Engineering*. 2017. 139(5): 51105 -51113.
188. Evans, A. T., Park, J. M., Chiravuri, S. and Gianchandani, Y. B. A Low Power, Microvalve Regulated Architecture for Drug Delivery Systems. *Biomedical microdevices*. 2010. 12(1): 159-68.
189. Evans, A. T., Chiravuri, S. and Gianchandani, Y. B. A Multidrug Delivery System Using a Piezoelectrically Actuated Silicon Valve Manifold with Embedded Sensors. *Journal of Microelectromechanical Systems*. 2011. 20(1): 231-238.
190. Morimoto, Y., Mukouyama, Y., Habasaki, S. and Takeuchi, S. Balloon Pump with Floating Valves for Portable Liquid Delivery. *Micromachines*. 2016. 7(3): 39-48.
191. Wei, X. and Liu, J. Power Sources and Electrical Recharging Strategies for Implantable Medical Devices. *Frontiers of Energy and Power Engineering in China*. 2008. 2(1): 1-13.
192. Rahimi-Eichi, H., Baronti, F. and Chow, M. Y. Online Adaptive Parameter Identification and State-of-Charge Coestimation for Lithium-Polymer Battery Cells. *IEEE Transactions on Industrial Electronics*. 2014. 61(4): 2053-2061.
193. Bullen, R. A., Arnot, T. C., Lakeman, J. B. and Walsh, F. C. Biofuel Cells and Their Development. *Biosensors and Bioelectronics*. 2006. 21(11): 2015-2045.

194. Drews, J., Fehrmann, G., Staub, R. and Wolf, R. Primary Batteries for Implantable Pacemakers and Defibrillators. *Journal of power sources*. 2001. 97-98: 747-749.
195. Mallela, V. S., Ilankumaran, V. and Rao, N. Trends in Cardiac Pacemaker Batteries. *Indian pacing and electrophysiology journal*. 2004. 4(4): 201-212.
196. Andrea, C., Alessandro, D., Emilio, S. and Mauro, S. Kinetic and Thermal Energy Harvesters for Implantable Medical Devices and Biomedical Autonomous Sensors. *Measurement Science and Technology*. 2014. 25(1): 012003-012016.
197. Settaluri, K. T., Lo, H. and Ram, R. J. Thin Thermoelectric Generator System for Body Energy Harvesting. *Journal of Electronic Materials*. 2012. 41(6): 984-988.
198. Selvan, K. V. and Mohamed Ali, M. S. Micro-Scale Energy Harvesting Devices: Review of Methodological Performances in the Last Decade. *Renewable and Sustainable Energy Reviews*. 2016. 54: 1035-1047.
199. Kim, H. S., Kim, J.-H. and Kim, J. A Review of Piezoelectric Energy Harvesting Based on Vibration. *International Journal of Precision Engineering and Manufacturing*. 2011. 12(6): 1129-1141.
200. Sohn, J. W., Choi, S. B. and Lee, D. Y. An Investigation on Piezoelectric Energy Harvesting for MEMS Power Sources. *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*. 2005. 219(4): 429-436.
201. Nasiri, A., Zabalawi, S. A. and Jeutter, D. C. A Linear Permanent Magnet Generator for Powering Implanted Electronic Devices. *IEEE transactions on power electronics*. 2011. 26(1): 192-199.
202. Dinis, H., Colmiais, I. and Mendes, P. Extending the Limits of Wireless Power Transfer to Miniaturized Implantable Electronic Devices. *Micromachines*. 2017. 8(12): 359-373.
203. Ackermann, D. M., Smith, B., Kilgore, K. L. and Peckham, P. H. Design of a High Speed Transcutaneous Optical Telemetry Link. *2006 International Conference of the IEEE Engineering in Medicine and Biology Society*. 30 August-3 September, 2006. IEEE. 2006. 2932-2935.

204. Christensen, D. B. and Roundy, S. Ultrasonically Powered Piezoelectric Generators for Bio-Implantable Sensors: Plate Versus Diaphragm. *Journal of Intelligent Material Systems and Structures*. 2016. 27(8): 1092-1105.
205. RamRakhyani, A. K., Mirabbasi, S. and Chiao, M. Design and Optimization of Resonance-Based Efficient Wireless Power Delivery Systems for Biomedical Implants. *IEEE transactions on biomedical circuits and systems*. 2011. 5(1): 48-63.
206. Zebda, A., Cosnier, S., Alcaraz, J. P., Holzinger, M., Le Goff, A., Gondran, C., Boucher, F., Giroud, F., Gorgy, K., Lamraoui, H. and Cinquin, P. Single Glucose Biofuel Cells Implanted in Rats Power Electronic Devices. *Scientific Reports*. 2013. 3: 1516-1520.
207. Lu, Q., Hutchings, G. S., Zhou, Y., Xin, H. L., Zheng, H. and Jiao, F. Nanostructured Flexible Mg-Modified LiMnPO<sub>4</sub> Matrix as High-Rate Cathode Materials for Li-Ion Batteries. *Journal of Materials Chemistry A*. 2014. 2(18): 6368-6373.
208. Farid Ullah, K. and Muhammad Usman, Q. State-of-the-Art in Vibration-Based Electrostatic Energy Harvesting. *Journal of Micromechanics and Microengineering*. 2016. 26(10): 103001-103028.
209. Saha, A., Iqbal, S., Karmaker, M., Zinnat, S. F. and Ali, M. T. A Wireless Optical Power System for Medical Implants Using Low Power near-IR Laser. *2017 39th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*. 11-15 July, 2017. IEEE. 2017. 1978-1981.
210. Maleki, T., Cao, N., Song, S. H., Kao, C., Ko, S. C. and Ziaie, B. An Ultrasonically Powered Implantable Micro-Oxygen Generator (Imog). *IEEE Transactions on Biomedical Engineering*. 2011. 58(11): 3104-3111.
211. Ho, J. S., Yeh, A. J., Neofytou, E., Kim, S., Tanabe, Y., Patlolla, B., Beygui, R. E. and Poon, A. S. Y. Wireless Power Transfer to Deep-Tissue Microimplants. *Proceedings of the National Academy of Sciences*. 2014. 111(22): 7974-7979.
212. Agarwal, K., Jegadeesan, R., Guo, Y. X. and Thakor, N. V. Wireless Power Transfer Strategies for Implantable Bioelectronics. *IEEE reviews in biomedical engineering*. 2017. 10: 136-161.



213. Chee, P. S., Rahim, R. A., Hashim, U., Arsat, R. and Leow, P. L. Low Cost Diffuser Based Micropump Using Pinch Actuation. *Advanced Materials Research*. 2012. 422: 397-400
214. Aldaoud, A., Soto-Breceda, A., Tong, W., Conductier, G., A Tonta, M., Coleman, H. A., Parkington, H. C., Clarke, I., Redoute, J.-M., Garrett, D. J. and Prawer, S. Wireless Multichannel Optogenetic Stimulators Enabled by Narrow Bandwidth Resonant Tank Circuits. *Sensors and Actuators A: Physical*. 2017. (In press).
215. Mohan, S. S., Hershenson, M. d. M., Boyd, S. P. and Lee, T. H. Simple Accurate Expressions for Planar Spiral Inductances. *IEEE journal of solid-state circuits*. 1999. 34(10): 1419-1424.
216. Sun, T., Xie, X. and Wang, Z. *Wireless Power Transfer for Medical Microsystems*. Beijin, China: Springer. 2013.
217. Grove, T. T., Masters, M. F. and Miers, R. E. Determining Dielectric Constants Using a Parallel Plate Capacitor. *American journal of physics*. 2005. 73(1): 52-56.
218. Mohamed Ali, M. S., Yuan, W. N. and Takahata, K. Analysis of Micropatterned Wireless Resonant Heaters for Wireless-Control of MEMS Thermal Actuators. *Microsystem Technologies*. 2014. 20(2): 235-241.
219. Mohamed Ali, M. S. and Takahata, K. Frequency-Controlled Wireless Shape-Memory-Alloy Microactuators Integrated Using an Electroplating Bonding Process. *Sensors and Actuators A: Physical*. 2010. 163(1): 363-372.
220. Guo, L., Guvanase, G. S., Liu, X., Tuthill, C., Nichols, T. R. and DeWeerth, S. P. A PDMS-Based Integrated Stretchable Microelectrode Array (Ismea) for Neural and Muscular Surface Interfacing. *IEEE transactions on biomedical circuits and systems*. 2013. 7(1): 1-10.
221. Bardaweel, H. K. and Bardaweel, S. K. Dynamic Simulation of Thermopneumatic Micropumps for Biomedical Applications. *Microsystem Technologies*. 2013. 19(12): 2017-2024.
222. Mitsuhsa, I., Keita, S., Shinya, K., Yasuhiro, K., Yohei, S. and Koichi, H. Evaluation Methodology of Gas Permeable Characterization in a Polymer-Based Microfluidic Device by Confocal Fluorescence Imaging. *Journal of Micromechanics and Microengineering*. 2012. 22(6): 065023-065031.

223. Erickson, D., Sinton, D. and Li, D. Joule Heating and Heat Transfer in Poly(Dimethylsiloxane) Microfluidic Systems. *Lab on a chip*. 2003. 3(3): 141-149.
224. Yi, P., Kayani, A. A., Chrimes, A. F., Ghorbani, K., Nahavandi, S., Kalantar-zadeh, K. and Khoshmanesh, K. Thermal Analysis of Nanofluids in Microfluidics Using an Infrared Camera. *Lab on a chip*. 2012. 12(14): 2520-2525.
225. Han-Sheng, C. and Steven, W. Design, Fabrication and Characterization of a Conducting PDMS for Microheaters and Temperature Sensors. *Journal of Micromechanics and Microengineering*. 2009. 19(4): 045010-045017.
226. Ren, H. and Wu, S.-T. Optical Lens. In: Ren, H. and Wu, S.-T. *Introduction to Adaptive Lenses*. NJ, USA: John Wiley & Sons, Inc. 1-22; 2012.
227. Fong, J., Xiao, Z. and Takahata, K. Wireless Implantable Chip with Integrated Nitinol-Based Pump for Radio-Controlled Local Drug Delivery. *Lab on a chip*. 2015. 15(4): 1050-1058.
228. Luo, T., Esfarjani, K., Shiomi, J., Henry, A. and Chen, G. Molecular Dynamics Simulation of Thermal Energy Transport in Polydimethylsiloxane. *Journal of applied physics*. 2011. 109(7): 074321-074327.
229. Orabona, E., Rea, I., Rendina, I. and Stefano, L. D. Numerical Optimization of a Microfluidic Assisted Microarray for the Detection of Biochemical Interactions. *Sensors*. 2011. 11(10): 9658-9666.
230. Rahimi, S., Sarraf, E. H., Wong, G. K. and Takahata, K. Implantable Drug Delivery Device Using Frequency-Controlled Wireless Hydrogel Microvalves. *Biomedical microdevices*. 2011. 13(2): 267-277.
231. Farra, R., Sheppard, N. F., McCabe, L., Neer, R. M., Anderson, J. M., Santini, J. T., Cima, M. J. and Langer, R. First-in-Human Testing of a Wirelessly Controlled Drug Delivery Microchip. *Science translational medicine*. 2012. 4(122): 122ra21.
232. COMSOL. *Comsol Multiphysics Reference Manual*. Burlington, MA, USA: COMSOL. 2015.
233. Hossain, S. and Kim, K.-Y. Mixing Analysis in a Three-Dimensional Serpentine Split-and-Recombine Micromixer. *Chemical Engineering Research and Design*. 2015. 100: 95-103.

234. John, V. Higher Order Finite Element Methods and Multigrid Solvers in a Benchmark Problem for the 3D Navier–Stokes Equations. *International Journal for Numerical Methods in Fluids*. 2002. 40(6): 775-798.
235. Mangold, M., Schmidt, J., Tobiska, L. and Tsotsas, E. Modeling of Membrane Reactors. In: Seidel-Morgenstern, A. *Membrane Reactors for Hydrogen Production Processes*. Weinheim, Germany: John Wiley & Sons. 29-62; 2010.
236. Sia, S. K. and Whitesides, G. M. Microfluidic Devices Fabricated in Poly (Dimethylsiloxane) for Biological Studies. *Electrophoresis*. 2003. 24(21): 3563-3576.
237. Yi, P., Awang, R. A., Rowe, W. S. T., Kalantar-zadeh, K. and Khoshmanesh, K. PDMS Nanocomposites for Heat Transfer Enhancement in Microfluidic Platforms. *Lab on a chip*. 2014. 14(17): 3419-3426.
238. Dardano, P., Calìo, A., Politi, J., Rea, I., Rendina, I. and De Stefano, L. Optically Monitored Drug Delivery Patch Based on Porous Silicon and Polymer Microneedles. *Biomedical Optics Express*. 2016. 7(5): 1645-1655.
239. Monti, G., Costanzo, A., Mastri, F. and Mongiardo, M. Optimal Design of a Wireless Power Transfer Link Using Parallel and Series Resonators. *Wireless Power Transfer*. 2016. 3(2): 105-116.
240. Massarini, A. and Kazimierczuk, M. K. Self-Capacitance of Inductors. *IEEE transactions on power electronics*. 1997. 12(4): 671-676.
241. Clayton, G., Tien, S., Fleming, A., Moheimani, S. and Devasia, S. Inverse-Feedforward of Charge-Controlled Piezopositioners. *Mechatronics*. 2008. 18(5): 273-281.
242. Rosa, E. B. and Grover, F. W. Formulas and Tables for the Calculation of Mutual and Self Inductance.(Revised.). *Journal of the Washington Academy of Sciences*. 1911. 1(1/2): 14-16.
243. Cannon, B. L., Hoburg, J. F., Stancil, D. D. and Goldstein, S. C. Magnetic Resonant Coupling as a Potential Means for Wireless Power Transfer to Multiple Small Receivers. *IEEE transactions on power electronics*. 2009. 24(7): 1819-1825.
244. Sugiyama, H. Performance Analysis of Magnetic Resonant System Based on Electrical Circuit Theory. In: Kim, K. Y. *Wireless Power Transfer-Principles and Engineering Explorations*. London, UK: InTech. 95-116; 2012.

245. Nafea, M., Mohamed, Z., Abdullahi, A. M., Ahmad, M. A. and Husain, A. R. Dynamic Hysteresis Based Modeling of Piezoelectric Actuators. *Jurnal Teknologi (Sciences and Engineering)*. 2014. 67(5): 9-13.
246. Qi, C., Gao, F., Li, H.-X., Li, S., Zhao, X. and Dong, Y. An Incremental Hammerstein-Like Modeling Approach for the Decoupled Creep, Vibration and Hysteresis Dynamics of Piezoelectric Actuator. *Nonlinear Dynamics*. 2015. 82(4): 2097-2118.
247. Inman, D. J. *Engineering Vibration*. 4th. ed. NJ, USA: Prentice Hall New Jersey. 2008.
248. Valentinuzzi, M. E. and Kohen, A. K. Laplace's Law: What It Is About, Where It Comes from, and How It Is Often Applied in Physiology [Retrospectroscope]. *IEEE pulse*. 2011. 2(4): 74-84.
249. Chee, P. S., Nafea, M., Leow, P. L. and Mohamed Ali, M. S. Wireless Powered Thermo-Pneumatic Micropump Using Frequency-Controlled Heater. *Sensors and Actuators A: Physical*. 2015. 233: 1-8.
250. Chee, P. S., Nafea, M., Leow, P. L. and Mohamed Ali, M. S. Thermal Analysis of Wirelessly Powered Thermo-Pneumatic Micropump Based on Planar LC Circuit. *Journal of Mechanical Science and Technology*. 2016. 30(6): 2659-2665.
251. Nafea, M., AbuZaiter, A., Kazi, S. and Ali, M. S. M. Frequency-Controlled Wireless Passive Thermopneumatic Micromixer. *Journal of Microelectromechanical Systems*. 2017. 26(3): 691-703.
252. Nafea, M., Schlosser, C., Kazi, S., Mohamed, Z. and Mohamed Ali, M. S. Optimal Two-Degree-of-Freedom Control for Precise Positioning of a Piezo-Actuated Stage. *International Journal of Integrated Engineering*. 2017. 9(4): 93-102.
253. Nafea, M., Kazi, S., Mohamed, Z. and Ali, M. M. A Hybrid Control Approach for Precise Positioning of a Piezo-Actuated Stage. *2014 14th International Conference on Control, Automation and Systems (ICCAS)*. 22-25 October, 2014. IEEE. 2014. 667-671.
254. Nafea, M., AbuZaiter, A., Faris, O., Kazi, S. and Ali, M. M. Selective Wireless Control of a Passive Thermopneumatic Micromixer. *2016 IEEE 29th International Conference on Micro Electro Mechanical Systems (MEMS)*. 24-28 January, 2016. IEEE. 2016. 792-795.

255. Nafea, M., Ahmad, N., Wahap, A. R. and Mohamed Ali, M. S. Modeling and Simulation of a Wireless Passive Thermopneumatic Micromixer. In: Mohamed Ali, M. S., Wahid, H., Mohd Subha, N. A., Sahlan, S., Md. Yunus, M. A. and Wahap, A. R. *Communications in Computer and Information Science Book Series*. Singapore: Springer Singapore. 312-322; 2017.