

AKUREYRI AIRPORT

- INTERNATIONAL GATEWAY

Akureyri International Airport has one runway which is 2,400 m long, 45 m wide and can safely accomodate the largest airplanes. The airport is controlled by highly qualified air traffic controllers (ATC). The approach control equipment and lighting system are up to the highest standards and include LOC, ILS and GPS approaches.

The fire and rescue service at the airport is in accordance with ICAO category 5 and can be raised to category 7 on request. There are always at least three (cat 5) to five (cat 7) employees on firefighting duty. Akureyri International Airport is located in North Iceland, which requires excellent winter services. The airport is very well equipped for snow removal and is open all year round. Further information can be found on www.akureyriairport.is



TECHNICAL

INFORMATION

ARP coordinates and site at Aerodrome	65°39′24″N 18°04′19″W Centre of Runway				
Direction and distance from the CITY	1.5 NM - 160° GEO				
Elevation/Reference temperature	7FT/11.3°C(July)				
Geoid undulation at AD ELEV PSN	217FT				
MAG VAR / Annual change	13°W(2015)/0.27° decreasing				
AD Administration, address,	Isavia Itd. Akureyri Airport				
telephone, telefax, AFS	Tel.: +354 424 4370				
	e-mail: biar@isavia.is				
	Control tower: Tel: +354 424 4360, Fax: +354 424 4390				
Types of traffic permitted	IFR-VFR				
Cargo handling facilities	Normal facilities available O/R				
Fuel/oil types	AVGAS 100LL, JP-A1/NIL				
Fuelling facilities / capacity	Delivery rate 150 liters per minute AVGAS / Delivery rate 650 liters per minute JP-A1				
De-icing facilities	O/R				
Hangar space available for visiting aircraft	NIL				
Repair facilities for visiting aircraft	Major, light aircraft. Minor, large aircraft				
Landing Aids	RWY 01: ILS/RNAV/NDB				
	RWY19: RNAV/NDB				
AD category for fire fighting	CAT V				
	CAT VII PN 10 min				
	Information tel.: +354 424 4360 / +354 424 4380				
	e-mail: biar@isavia.is				
Runway length, width and strength	2400x45 m / PCN 45 / F/A/X/T				
Apron surface and strength	Asphalt 88,5x147 m / PCN 45 / F/A/X/T				
Taxiway width, surface and strength	Asphalt 78 m wide / PCN 45 / F/A/X/T				
Landing charges	Information on landing charges can be found on www.akureyriairport.is				
Passenger charges	Information on passenger charges can be found on www.akureyriairport.is				
Security charges	Information on security charges can be found on www.akureyriairport.is				
Operational hours	0700 - 2300				
	Service provided outside of operational hours upon request				

RWY designator	APCHLGT type LENINTST	THR LGT color WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY Centre line LGT length, spacing color, INTST	RWY edge LGT LEN, spacing color INTST	RWY End LGT color WBAR	SWY LGT LEN (M) color	Remarks
1	2	3	4	5	6	7	8	9	10
01	900 m LIH Crossbar 300 m 9 LDIN flashing lights with 700 m interval Lights start at 7196 m south of RWY 01	green	PAPI 3,5° (53.0 FT) and PAPI 5.3° (180.4FT)	NIL	NIL	LIHW	RED	NIL	RWY 01: PAPI lights 3.5° left side of RWY PAPI lights 5.3° right side of RWY
19	NIL	green	PAPI 3°	NIL	NIL	LIH	RED	NIL	TWY-apron LIL B THE ID LGT RWY01/19FLG WHITE